

EVXLF24H series

Product code	L ₁ , min mH	L ₂ , min mH	DCR ₁ , max Ω	DCR ₂ , max Ω	Rated current A _{rms}
EVXLF24H-0120	1.20	1.20	0.08	0.08	3.0
EVXLF24H-0250	2.50	2.50	0.17	0.17	2.0
EVXLF24H-0390	3.90	3.90	0.21	0.21	1.8
EVXLF24H-0450	4.50	4.50	0.24	0.24	1.5
EVXLF24H-0560	5.60	5.60	0.30	0.30	1.4
EVXLF24H-0680	6.80	6.80	0.40	0.40	1.2
EVXLF24H-0750	7.50	7.50	0.42	0.42	1.2
EVXLF24H-0820	8.20	8.20	0.53	0.53	1.1
EVXLF24H-1000	10.00	10.00	0.55	0.55	1.0
EVXLF24H-1500	15.00	15.00	0.75	0.75	0.8
EVXLF24H-1800	18.00	18.00	0.82	0.82	0.8
EVXLF24H-2000	20.00	20.00	1.00	1.00	0.7
EVXLF24H-2700	27.00	27.00	1.20	1.20	0.7
EVXLF24H-3500	35.00	35.00	1.75	1.75	0.5

All dimensions in mm

