

PRODUCT NUMBER NOTE 5, 7	SIZE NOTE 5	TAIL LENGTH DIM H	DIM D	DIM G	DIM E	OVERALL LENGTH DIM L	PLATING NOTE 11
67289-XXX	2 x XXX	.177/4.50	NOTE 4	.37/9.4+D DIM	.40/10.2+D DIM	.48/12.2+D DIM	30u"/.76u MIN Au OVER 50u"/1.27u Ni
67290-XXX		.177/4.50					15u"/.38u MIN Au OVER 50u"/1.27u Ni
67291-XXX		.177/4.50					GOLD FLASH OVER 50u"/1.27u Ni
67292-XXX		.177/4.50					120u"/3.05u 93/7 Sn/Pb OVER 50u"/1.27u Ni
67958-XXX		.310/7.90					30u"/.76u MIN Au OVER 50u"/1.27u Ni
67961-XXX		.310/7.90					15u"/.38u MIN Au OVER 50u"/1.27u Ni
68251-XXX		.680/17.30					30u"/.76u MIN Au OVER 50u"/1.27u Ni
68509-XXX		.480/12.20					30u"/.76u MIN Au OVER 50u"/1.27u Ni
68521-XXX		.480/12.20					30u"/.76u MIN GXT™ OVER 50u"/1.27u Ni
68830-XXX		.680/17.30					15u"/.38u MIN Au OVER 50u"/1.27u Ni
68831-XXX		.480/12.20					15u"/.38u MIN Au OVER 50u"/1.27u Ni
68832-XXX		.310/7.90					15u"/.38u MIN GXT™ OVER 50u"/1.27u Ni
68833-XXX		.310/7.90					30u"/.76u MIN GXT™ OVER 50u"/1.27u Ni
68834-XXX		.177/4.50					15u"/.38u MIN GXT™ OVER 50u"/1.27u Ni
68835-XXX		.177/4.50					30u"/.76u MIN GXT™ OVER 50u"/1.27u Ni
68836-XXX		.680/17.30					30u"/.76u MIN GXT™ OVER 50u"/1.27u Ni
68837-XXX		.680/17.30					15u"/.38u MIN GXT™ OVER 50u"/1.27u Ni
68838-XXX		.480/12.20					15u"/.38u MIN GXT™ OVER 50u"/1.27u Ni
69275-XXX		.310/7.90					GOLD FLASH OVER 50u"/1.27u Ni
69276-XXX		.310/7.90					120u"/3.05u 93/7 Sn/Pb OVER 50u"/1.27u Ni
69277-XXX		.480/12.20					GOLD FLASH OVER 50u"/1.27u Ni
69278-XXX		.480/12.20					120u"/3.05u 93/7 Sn/Pb OVER 50u"/1.27u Ni
69279-XXX		.680/17.30					GOLD FLASH OVER 50u"/1.27u Ni
69280-XXX		.680/17.30					120u"/3.05u 93/7 Sn/Pb OVER 50u"/1.27u Ni
69283-XXX		.177/4.50					DUPLEX 15u"/.38u Au & 100u"/1.27u 60/40 SnPb OVER 50u"/1.27u Ni
69284-XXX		.177/4.50					DUPLEX 30u"/.76u Au & 100u"/1.27u 60/40 SnPb OVER 50u"/1.27u Ni
69285-XXX		.310/7.90					DUPLEX 15u"/.38u Au & 100u"/1.27u 60/40 SnPb OVER 50u"/1.27u Ni
69286-XXX		.310/7.90					DUPLEX 30u"/.76u Au & 100u"/1.27u 60/40 SnPb OVER 50u"/1.27u Ni
69287-XXX		.480/12.20					DUPLEX 15u"/.38u Au & 100u"/1.27u 60/40 SnPb OVER 50u"/1.27u Ni
69288-XXX		.480/12.20					DUPLEX 30u"/.76u Au & 100u"/1.27u 60/40 SnPb OVER 50u"/1.27u Ni
69289-XXX		.680/17.30					DUPLEX 15u"/.38u Au & 100u"/1.27u 60/40 SnPb OVER 50u"/1.27u Ni
69290-XXX	2 x XXX	.680/17.30	NOTE 4	.37/9.4+D DIM	.40/10.2+D DIM	.48/12.2+D DIM	DUPLEX 30u"/.76u Au & 100u"/1.27u 60/40 SnPb OVER 50u"/1.27u Ni

NOTES:

① MOLDING MATERIAL: HI-TEMP RESIN
PER UL 94V-0
COLOR: NATURAL

② TERMINAL MATERIAL: 3/4 HARD PHOS BRONZE
UNS C5100.

3. PIN RETENTION TO BE 3 LBS/1.36 KG
MIN PER PIN IN EITHER DIRECTION.

④ DIM D =(NO. OF COLUMNS-1)TIMES .100/2.54

⑤ -XXX REPRESENTS NO. OF COLUMNS
(i.e. 2X5 PART IS -005)
-001 THRU -004 ARE NOT AVAILABLE
-005 THRU -050 ARE AVAILABLE

⑥ FLATNESS IS MEASURED FROM THE BOTTOM
OF THE END STANDOFFS.

⑦ ADD "LF" SUFFIX AT THE END OF PART NUMBER FOR LEAD FREE OPTION.

⑧ IF "LF" P/N THE PRODUCT MEETS EUROPEAN UNION
DIRECTIVES AND OTHER COUNTRY REGULATION AS
DESCRIBED IN GS-22-008.

⑩ THE PRODUCT IS NOT INTENDED TO BE EXPOSED
TO A MANUFACTURING SOLDER PROCESS.

⑪ PLATING OPTIONS:
MAY BE EITHER GOLD OR GXT PLATED AT MANUFACTURER'S OPTION.

mat'l. code		surface ISO 1302	tolerance ISO 1101	projection	product family HEADERS
ltr	ecn no	dr	date	tolerances unless otherwise specified	title
v				angles	VERTICAL 2-ROW GUIDE PIN
				linear	(SLOTTED) HEADER-PRESS FIT TAILS
				0°±2'	scale 2:1
				dr	M. FETROW 11/14/94
				engr	L. FYE 11/14/94
				chr	L. FYE 11/14/94
				appd	L. FYE 11/14/94
sheet	revision				type Product Customer Drawing
index	sheet				



FDconnect.com

Copyright FCI

1		2		3		4		5		6					
PRODUCT NUMBER NOTE 5,7		SIZE NOTE 5		TAIL LENGTH DIM H		DIM D		DIM G		DIM E		OVERALL LENGTH DIM L		PLATING NOTE 11	
67289-XXXLF		2 x XXX		.177/4.50		NOTE 4		.37/9.4+D DIM		.40/10.2+D DIM		.48/12.2+D DIM		30u"/.76u MIN Au OVER 50u"/1.27u Ni	
67290-XXXLF				.177/4.50										15u"/.38u MIN Au OVER 50u"/1.27u Ni	
67291-XXXLF				.177/4.50										GOLD FLASH OVER 50u"/1.27u Ni	
67292-XXXLF				.177/4.50										100u"/2.54u Sn OVER 50u"/1.27u Ni	
67958-XXXLF				.310/7.90										30u"/.76u MIN Au OVER 50u"/1.27u Ni	
67961-XXXLF				.310/7.90										15u"/.38u MIN Au OVER 50u"/1.27u Ni	
68251-XXXLF				.680/17.30										30u"/.76u MIN Au OVER 50u"/1.27u Ni	
68509-XXXLF				.480/12.20										30u"/.76u MIN Au OVER 50u"/1.27u Ni	
68521-XXXLF				.480/12.20										30u"/.76u MIN GXT™ OVER 50u"/1.27u Ni	
68830-XXXLF				.680/17.30										15u"/.38u MIN Au OVER 50u"/1.27u Ni	
68831-XXXLF				.480/12.20										15u"/.38u MIN Au OVER 50u"/1.27u Ni	
68832-XXXLF				.310/7.90										15u"/.38u MIN GXT™ OVER 50u"/1.27u Ni	
68833-XXXLF				.310/7.90										30u"/.76u MIN GXT™ OVER 50u"/1.27u Ni	
68834-XXXLF				.177/4.50										15u"/.38u MIN GXT™ OVER 50u"/1.27u Ni	
68835-XXXLF				.177/4.50										30u"/.76u MIN GXT™ OVER 50u"/1.27u Ni	
68836-XXXLF				.680/17.30										30u"/.76u MIN GXT™ OVER 50u"/1.27u Ni	
68837-XXXLF				.680/17.30										15u"/.38u MIN GXT™ OVER 50u"/1.27u Ni	
68838-XXXLF				.480/12.20										15u"/.38u MIN GXT™ OVER 50u"/1.27u Ni	
69275-XXXLF				.310/7.90										GOLD FLASH OVER 50u"/1.27u Ni	
69276-XXXLF				.310/7.90										100u"/2.54u Sn OVER 50u"/1.27u Ni	
69277-XXXLF				.480/12.20										GOLD FLASH OVER 50u"/1.27u Ni	
69278-XXXLF				.480/12.20										100u"/2.54u Sn OVER 50u"/1.27u Ni	
69279-XXXLF				.680/17.30										GOLD FLASH OVER 50u"/1.27u Ni	
69280-XXXLF				.680/17.30										100u"/2.54u Sn OVER 50u"/1.27u Ni	
69283-XXXLF				.177/4.50										DUPLEX 15u"/.38u Au & 100u"/2.54u Sn OVER 50u"/1.27u Ni	
69284-XXXLF				.177/4.50										DUPLEX 30u"/.76u Au & 100u"/2.54u Sn OVER 50u"/1.27u Ni	
69285-XXXLF				.310/7.90										DUPLEX 15u"/.38u Au & 100u"/2.54u Sn OVER 50u"/1.27u Ni	
69286-XXXLF				.310/7.90										DUPLEX 30u"/.76u Au & 100u"/2.54u Sn OVER 50u"/1.27u Ni	
69287-XXXLF				.480/12.20										DUPLEX 15u"/.38u Au & 100u"/2.54u Sn OVER 50u"/1.27u Ni	
69288-XXXLF				.480/12.20										DUPLEX 30u"/.76u Au & 100u"/2.54u Sn OVER 50u"/1.27u Ni	
69289-XXXLF				.680/17.30										DUPLEX 15u"/.38u Au & 100u"/2.54u Sn OVER 50u"/1.27u Ni	
69290-XXXLF		2 x XXX		.680/17.30		NOTE 4		.37/9.4+D DIM		.40/10.2+D DIM		.48/12.2+D DIM		DUPLEX 30u"/.76u Au & 100u"/2.54u Sn OVER 50u"/1.27u Ni	

mat'l. code				surface		tolerance		projection		product family	
ISO 1502				ISO 1502		ISO 1101				HEADERS	
litr				ecr no		dr		date		title	
V										VERTICAL 2-ROW GUIDE PIN	
				angles		linear		INCH/MM		(SLOTTED) HEADER-PRESS FIT TAILS	
				0° ± 2'		XXX ± .01/XXX ± .03		scale 2:1		dwg no	
						XXX ± .005/XXX ± .013				sheet 3 of 3 size	
						XXXX ± .0020/XXXX ± .005				67289	
				dr		M. FETROW				A3	
				engr		L. FYE				type	
				chr		L. FYE				Product Customer Drawing	
				appd		L. FYE					
sheet		revision									
index		sheet									

form A3

1

2

3

4

5

6

form A3