

Power Cord with Nema- Line Plug 3-pole, angled

new

**Description**

Power Supply Cord, Protection class I, Pin temperature 70 °C, Cable

**Approvals**



- UL License Number: E45116
- CSA License Number: 32338

**Weblinks**

Approvals, RoHS, CHINA-RoHS, e-Store, SCHURTER-Stock-Check, Distributor-Stock-Check, Product Configurator

**Technical Data**

Ratings IEC	10A / 250VAC; 50Hz
Ratings UL/CSA	10A / 250VAC; 60Hz
Dielectric Strength	> 4 kVDC between L-N > 2 kVAC between L/N-PE (1 min/50Hz)
Allowable Operation Temp.	-25 °C to 70 °C
Degree of Protection	from front side IP 20 acc. to IEC 60529
Protection Class	Suitable for appliances with protection class I acc. to IEC 61140
Terminal	moulded
Material: Housing	black or grey

**Dimensions**Length  24 mm

## Order Code

Product Configurator

## 1140 - R - Type - D - Length

The characters are placeholders for the correspondingly keys of selections from the key tables.  
Typ steht für die Dose bzw. 2. Seite, Länge ist die Leitungslänge in mm.

1140 - **R** - Type - D - Length = corde type

corde type	Configuration key
SVT 3x18AWG	N
SJT 3x18AWG	P
special cord	Z

General Product Information see page XXX

1140 - R - **Type** - D - Length = cord end 2

cord end 2
zzzz, <a href="#">2512</a> , <a href="#">2530</a> , <a href="#">3011</a> , <a href="#">3012</a> , <a href="#">3013</a> , <a href="#">302U</a> , <a href="#">3020</a> , <a href="#">3027</a> , <a href="#">3030</a> , <a href="#">311L</a> , <a href="#">312L</a>

1140 - R - Type - **D** - Length = Color

Color	Configuration key
jet black; RAL9005	A
silver grey; RAL7001	B

Standard color: black

1140 - R - Type - D - **Length** = Leitungslänge

Leitungslänge
zzzz, 000500, 001000, 001500, 002000, 002500, 003000, 005000

cord length in mm