

**Mates w/ Series 310...023 Surface Mount Z-Bend Socket (See Fig. 3)**

**Fig. 1**

- Series 351 and 800 horizontal Surface Mount headers are available with 0,46 dia. pluggable pins (MM #5102) and 0,71 dia. pluggable pins (MM #1502). See page 185 for details.
- Series 310 horizontal Surface Mount Z-Bend sockets use MM #1023 receptacles that accept pin diameters from 0,38 - 0,64. Series 801 use MM #1303 receptacles that accept pin diameters from 0,64 - 0,94 and 0,64 square leads. See pages 142 and 150 for details.
- Insulators are high temp. thermoplastic.



**Mates w/ Series 801...002 Surface Mount Z-Bend Socket (See Fig. 4)**

**Fig. 2**

<b>Ordering Information</b>	
<b>Fig. 1</b>	<b>Series 351...002    0,46 Dia. Surface Mount Header</b>  351-10-1 __ -40-002000 <b>Specify # of pins</b> →    02-10
	<b>Series 800...002    0,71 Dia. Surface Mount Header</b>  800-10-0 __ -40-002000 <b>Specify # of pins</b> →    02-10

**Mates w/ Series 351...002 Surface Mount Header (See Fig. 1)**

**Fig. 3**

For Electrical, Mechanical & Environmental Data, See pg. 4
For RoHS compliance select ◇ plating code.

PLATING CODE =	10 ◇			
Pin Plating	0,25µm Au			

**Mates w/ Series 800...002 Surface Mount Header (See Fig. 2)**

**Fig. 4**

<b>Fig. 3</b>	<b>Series 310...023    0,46 Dia. SMT Z-Bend Socket</b>  310-43-1 __ -40-023000 <b>Specify # of pins</b> →    02-10
	<b>Series 801...002    0,71 Dia. SMT Z-Bend Socket</b>  801-XX-0 __ -40-002000 <b>Specify # of pins</b> →    02-10

For Electrical, Mechanical & Environmental Data, See pg. 4
XX=Plating Code See Below
For RoHS compliance select ◇ plating code.

SPECIFY PLATING CODE XX=		93	99	43 ◇	44 ◇
Sleeve (Pin)		5,08µm Sn/Pb	5,08µm Sn/Pb	5,08µm Sn	5,08µm Sn
Contact (Clip)		0,76µm Au	5,08µm Sn/Pb	0,76µm Au	5,08µm Sn