



MAST - MICROWAVE ASSEMBLIES, SYSTEMS & TECHNOLOGIES

100 Davids Drive, Hauppauge, NY 11788


Tel: (631) 436-7400

FAX: (631) 436-9219

Digital SP2T Switch

MODEL: SW2-200305RD2NF

Frequency	20GHz-30.5GHz
Insertion Loss:.....	3dB max.
Input/Output VSWR.....	2.0:1 max.
Isolation.....	30 dB min.
Switching Speed.....	30nS max.
DC power.....	+5VDC,-5VDC
Control input	1bit TTL



Features

New Product Announcement
January 24, 2008

MITEQ, Inc. introduces a reflective Single Pole Two Throw Switch covering the frequency range from 20GHz to 30.5 GHz with a minimum of 30dB isolation and VSWR of 2.0:1 max. The 1 bit input control word is TTL compatible and commands switching time from 50% control input to the 10%/90% settling within 30nS. Rise/Fall time <20ns typical. The power handling is 20dBm. Options available include an extended band and sub band versions. Please consult the factory for further information.

MITEQ, Inc.
100 Davids Drive
Hauppauge, NY 11788
631-436-7400






MAST - MICROWAVE ASSEMBLIES, SYSTEMS & TECHNOLOGIES

100 Davids Drive, Hauppauge, NY 11788

Tel: (631) 436-7400

FAX: (631) 436-9219

Typical Test Data



Outline Drawing

