


High Frequency Surface Mount Attenuators



PAT Series

- Frequency operation to 10 GHz
- Industry standard 0805, 1206, 1612 chip sizes
- Low parasitic capacitance and inductance
- Thin film stability over time and temperature

The PAT chip attenuator series are available in a wide range of power ratings from 100mW to 250mW. The surface mount package is ideal for applications where parasitic capacitance and inductance are concerns. Typical applications include wireless communication receivers and transmitters.

Electrical Data

	PAT1220	PAT1632	PAT3042SC	PAT3042SD
Impedance	50	50	50	75
Frequency Range	DC to 10 GHz	DC to 3GHz	DC to 3GHz	DC to 2GHz
VSWR	1.3	1.3	1.2	1.3
Attenuation	0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10dB	0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 16dB	0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 16, 20dB	
Attenuation Tolerance	±0.3dB	0 to 10dB: ±0.3dB 16dB: ±0.5dB	0 to 10dB: ±0.3dB 16, 20dB: ±0.5dB	
TCR	±50ppm/°C	±50ppm/°C	±25ppm/°C	
Power Rating	100mW	125mW	250mW	
Operating Temperature Range	-55°C to +125°C			

Environmental Data




	Test Condition	Tolerance	
		Attenuation	Δ Impedance
Short Time Overload	2.5 x rated voltage, 5 sec	±0.02dB	±0.2%
Load Life	1000 Hours, 70°C	±0.04dB	±0.5%
Moisture Resistance	1000 Hours, 60°C, 95%	±0.04dB	±0.5%
Temperature Cycle	5 Cycles, 125°C High, -55 Low	±0.02dB	±0.2%
Resistance to Solder Heat	260°C, 10 sec.	±0.02dB	±0.2%
Terminal Strength	Fulcrum dist: 90mm, Bending width: 3mm Substrate: Glass epoxy t=1.6mm	±0.02dB	±0.2%
Solderability	235°C, 3 sec.	>95% coverage	
Insulation Resistance	500V, 1 minute	>1000M	

General Note

IRC reserves the right to make changes in product specification without notice or liability. All information is subject to IRC's own data and is considered accurate at time of going to print.


High Frequency Surface Mount Attenuators

Physical Data





High Frequency Surface Mount Attenuators

Power Derating Curve



Schematic Diagram Data



Ordering Data

Prefix **HFR** - **PAT1220** - **C** - **3dB** - **T(5)**

Model
 PAT1220; PAT1632; PAT3042SD (75Ω);
 PAT3042SC(50Ω)

Attenuation
 0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 16, 20dB

Impedance
 C = 50Ω; D = 75Ω

Package
 T=Tape, B=Bulk, Taping Quantity Unit: 5 (5000), 4 (1000)