



#### General ordering data

Order No.	1860021000
Part designation	SAIL-FCG-3P-10U
Version	Sensor/Actuator line, One end without connector, LED: No, 10.00 m, PUR/PVC
EAN	4032248416127
Qty.	1 pc(s).

#### Technical data

Ambient temperature, max.	90 °C
Ambient temperature, min.	-30 °C
Cable connection diameter	4.3
Cable diameter, max.	5 mm
Cable diameter, min.	4.6 mm
Connection cross-section	0.34...0.5
Contact material	Ni/Au
Contact surface	gold-plated
Contact tube diameter	Miscellaneous
Core cross-section	0.34 mm <sup>2</sup>
Material	PUR/PVC
Protection class	IP 67
Rated current	4 A
Rated voltage	250 V DC / 300 V AC
Sheathing colour	black
Wiring diagram	
No. of poles	3
Version	straight
Cable length	10 m

#### Classifications

ETIM 2.0	EC000304
ETIM 3.0	EC001855
eClass 4.1	27-06-00-00
eClass 5.0	27-06-91-90
eClass 5.1	27-06-91-90

## Classifications

### Similar products

Order No.	Part designation	Version
1860020150	SAIL-FCG-3P-1.5U	Sensor/Actuator line, One end without connector, LED: No, 1.50 m, PUR/PVC
1860020300	SAIL-FCG-3P-3.0U	Sensor/Actuator line, One end without connector, LED: No, 3.00 m, PUR/PVC
1860020500	SAIL-FCG-3P-5.0U	Sensor/Actuator line, One end without connector, LED: No, 5.00 m, PUR/PVC