


Flachstecker
mit Steckerbreite **6,3 mm**
zum Einrasten in Gehäuse



Tabs
with tab width **6.3 mm**
to engage in housings

Typ 1



Typ	Nenn- quer- schnitt qmm	Steck- dicke	Steck- breite	a1	a2	L1	L2	Mat- dicke	Form E=Einzel B=Band	Teile-Nr.	Werkstoff	Oberfläche	Verb- vor- schub
1	0,5 - 1	0,80	6,30	8,20	4,00	28,00	16,00	0,37	B	26512.126.009	CuZn	IrSn 3	L
									B	26512.126.179	CuZn		
									B	26512.201.179	CuSn		
									E	46512.126.009	CuZn		
									E	46512.201.179	CuSn		
1	1,5 - 2,5	0,80	6,30	8,20	4,00	28,00	16,00	0,37	B	26513.126.009	CuZn	IrSn 3	L
									B	26513.126.179	CuZn		
									B	26513.201.179	CuSn		
									B	26513.213.009	CuSn		
									E	46513.126.009	CuZn		
1	4 - 6	0,80	6,30	8,20	4,00	28,00	16,00	0,37	B	26514.126.009	CuZn	IrSn 3	L
									B	26514.126.179	CuZn		
									B	26514.201.179	CuSn		
									B	26514.213.009	CuSn		
									E	46514.126.009	CuZn		
									E	46514.201.179	CuSn	IrSn 3	

16130.004