









FIG. 1

DIMENSIONS ARE IN INCHES		UNLESS OTHERWISE NOTED	TOLERANCES ARE:	TITLE:	DWG NO:
ONE PLACE DECIMALS $\pm .1[2.5]$	THREE PLACE DECIMALS $\pm .005[.127]$	ANGLES $\pm 2^\circ$		ELEVATED SQT ASSM	ESQT-1XX-XX-XX-X-XXX-XXX-XX
TWO PLACE DECIMALS $\pm .01[.25]$	FOUR PLACE DECIMALS $\pm .0020[.051]$				SHEET 1 OF 2

DO NOT SCALE
FROM THIS PRINT

**** - MW OPTION, DO NOT DESIGN IN. SAMTEC WILL ONLY SUPPORT EXISTING BUSINESS 2/07/02.**

- ESQT-1XX-XX-XX-X-XXX-XXX-XX
- POSITION SPECIFICATION**
-02 THRU -50 POSITIONS PER ROW (SEE NOTE 1)
- LEAD STYLE SPEC**
-02: USE C-79-02-XX
-03: USE C-79-53-XX
- PLATING SPECIFICATION**
-F: FLASH SELECTIVE GOLD (USE C-79-XX-F)
-FM: FLASH SELECTIVE, MATTE TIN REMAINDER (USE C-79-XX-F)
-L: LIGHT SELECTIVE (USE C-79-XX-L)
-LM: LIGHT SELECTIVE, MATTE TIN REMAINDER (USE C-79-XX-L)
-S: SELECTIVE (USE C-79-XX-S)
-SM: SELECTIVE, MATTE TIN REMAINDER (USE C-79-XX-S)
-M: MEDIUM SELECTIVE (USE C-79-XX-M)
-MM: MEDIUM SELECTIVE, MATTE TIN REMAINDER (USE C-79-XX-M)
-H: HEAVY GOLD (USE C-79-XX-H)
-G: GOLD (USE C-79-XX-G)
-GF: LIGHT GOLD, GOLD FLASH REMAINDER (-02 LEAD STYLE ONLY. USE C-79-02-GF)
- OPTION**
**-MW: METAL WASHER (SEE FIG. 2, SHT. 2) (5 POS. MIN, 30 POS MAX) (USE TMMH-XX-D-XX-XX BODY) (N/A ON -S ROW SPEC) (.090 [2.29] MIN, .300 [7.62] MAX TAIL FOR -F, -L & -S PLATING) (.090 [2.29] MIN, .482 [12.24] MAX TAIL FOR -G & -M PLATING)
- POLARIZATION OPTION**
-XXX INDICATES POSITION (SEE FIG 3, SHT. 2) (USE PK-07-N)
- SPACE OPTION**
-XXX [7.65] MIN FOR -S, -D, -Q ROWS
.375 [9.53] MIN FOR -T, -5 & -6 ROWS
"B" MAX (SEE TABLE 2)
- ROW SPECIFICATION**
-S: SINGLE (SEE -S)
-D: DOUBLE (SEE -D)
-T: TRIPLE (SEE -T & SEE NOTE 4)
-Q: QUAD (SEE -Q)
-5: FIVE (SEE -5 & SEE NOTE 4)
-6: SIX (SEE -6 & SEE NOTE 4)



PROPRIETARY NOTE

THIS DOCUMENT CONTAINS INFORMATION CONFIDENTIAL AND PROPRIETARY TO SAMTEC INC. AND SHALL NOT BE REPRODUCED OR TRANSMITTED TO OTHER DOCUMENTS OR DISCLOSED TO OTHERS OR USED FOR ANY PURPOSE OTHER THAN THAT FOR WHICH IT WAS OBTAINED WITHOUT THE EXPRESSED WRITTEN CONSENT OF SAMTEC INC.

NOTE:

1. TOOLING TO BE DESIGNED TO PRODUCE UP TO 61 POSITIONS.
2. THIS NOTE WAS DELETED.
3. TMM/TMMH BODIES ARE NOT TO BE MORE THAN $\pm .005$ FROM PLANE SET BY SQT BODY.
4. -XM FOR T, 5 AND 6 ROW OPTIONS CANNOT WITHSTAND PB-FREE REFLOW PROCESSING.
5. MAX CUT FLASH .020[.51]

TABLE 2		
LEAD STYLE	"A"	"B"
-02	.850 [21.59]	.800 [20.32]
-03	.458 [11.63]	.408 [10.36]

PLOT SCALE: 1=.44 / DIMSCALE: .3

CONTACT:
PHOS BRONZE
MATERIAL:
COLOR: BLACK LCP

samtec

520 PARK EAST BLVD. NEW ALBANY, INDIANA 47150
PHONE (812) 944-6733 P.O. BOX 1147
CODE 55322

MADE BY:
PURVIS 10-20-95

ESQT-1XX-XX-XX-X-XXX-XXX-XX
SHEET 1 OF 2

MISC\MKGT
ESQT-ASM