

- Our lowest profile DIP sockets with an above PCB height of .095".
- Special short, Hi-Rel, 4-finger BeCu #12 clip rated at 3 amps. See page 207 for details.
- Uses Mill-Max #1534 pin. See page 130 for details.

Total number of pins				Quantity per tube	<h3 style="margin: 0;">Ordering Information</h3>	
	A	B	C			
	6	0.3	0.3			
8	0.4	0.3	0.4	50		
14	0.7	0.3	0.4	28		
16	0.8	0.3	0.4	25		
18	0.9	0.3	0.4	22		
20	1.0	0.3	0.4	20		
22	1.1	0.3	0.4	18		
24	1.2	0.3	0.4	16		
28	1.4	0.3	0.4	14		
20	1.0	0.4	0.5	20		
22	1.1	0.4	0.5	18		
24	1.2	0.4	0.5	16		
28	1.4	0.4	0.5	14		
24	1.2	0.6	0.7	16		
28	1.4	0.6	0.7	14		
32	1.6	0.6	0.7	12		
36	1.8	0.6	0.7	11		
40	2.0	0.6	0.7	10		
48	2.4	0.6	0.7	8		
50	2.5	0.6	0.7	8		

*XX= Plating Code
See Below*

For RoHS compliance, select \diamond plating code. For the all gold option (XX=13) also change part number from 115-XX-XXX-41-003000 to 115-13-XXX-41-003100

RoHS
2002/95/EC

SPECIFY PLATING CODE XX=	13 \diamond		93	99		43 \diamond	44 \diamond
Sleeve (Pin)	10 μ " Au		200 μ " Sn/Pb	200 μ " Sn/Pb		200 μ " Sn	200 μ " Sn
Contact (Clip)	30 μ " Au		30 μ " Au	200 μ " Sn/Pb		30 μ " Au	200 μ " Sn