



250 Series—Male Tabs

①



18RA-250T
vinyl self-insulated
installing tools—WT145C,
WT2000, ERG-2001,
ERG-2003, WT1455,
WT112M

②



18RA-251T
nylon fully insulated
installing tools—WT145C,
WT2000, ERG-2001,
ERG-2003, WT1455,
WT112M

③



18RAS-251TX
heat shrinkable nylon fully
insulated
installing tool—WT1255

④



A18-250T
Non-insulated/insulated grip
installing tool—WT110M

⑤



18-251T
Non-insulated
installing tools—WT110M,
WT111M, WT2000,
ERG-2002, WT1300,
WT112M, ERG-2002, WT1300, WT112M

Cat. No.	Bulk Cat. No.	Pkg. Qty.	Wire Range	Max. Ins.	Tab Size	Wt./lbs. Per 1000	Dimensions	
							A	B
① 18RA-250T	RA2517	100/1M	22-18	.150	.250 x .032	3	.95	—
14RB-250T	RB2517	100/1M	16-14	.170	.250 x .032	3	.95	—
10RC-250T	RC2517	50/500	12-10	.250	.250 x .032	4	1.08	—
② 18RA-251T	RA25177	50/500	22-18	.150	.250 x .032	5	1.13	.45
14RB-251T	RB25177	50/500	16-14	.170	.250 x .032	5	1.13	.45
10RC-251T	RC25177	25/250	12-10	.210	.250 x .032	5	1.17	.45
③ 18RAS-251TX	—	50	22-18	.170	.250 x .032	4	1.80	—
14RBS-251TX	—	100	16-14	.200	.250 x .032	5	1.75	—
10RCS-251TX	—	100	12-10	.250	.250 x .032	6	1.80	—
④ A18-250T	—	100	22-18	—	.250 x .032	3	.87	—
B14-250T	—	100	20-14	—	.250 x .032	3	.87	—
⑤ A18-251T	A251	100/1M	22-18	—	.250 x .032	2	.68	—
B14-251T	B251	100/1M	16-14	—	.250 x .032	2	.68	—
C10-251T	—	50	12-10	—	.250 x .032	2	.68	—

Material: brass
Finish: tin plated

Most standard bulk catalogue numbers can be put on Mylar Tape for reel fed applications (12050 tool and application dies). See page C61.

Please put the suffix M for Mylar Tape RA2573M. (Bulk number 1000 and 500 packages.)

For Mil Specs listing, please refer to page C73.

