



NOTES:

ELECTRICAL:

1. VOLTAGE RATING : 125 VAC RMS.
2. CURRENT RATING : 1.5 AMP.
3. CONTACT RESISTANCE : 45 MILLIOHMS MAX.
4. INSULATION RESISTANCE: 1000 MEGOHMS MIN @ 500 VDC.
5. DIELECTRIC STRENGTH : 1000 VAC RMS 60Hz, 1MIN.

MECHANICAL:

1. HOUSING & INSERT MATERIAL: GLASS FILLED NYLON UL94V-0, COLOR:BLACK
2. CONTACT MATERIAL : PHOSPHOR BRONZE ϕ 0.46mm.
OR PHOSPHOR BRONZE t=0.35mm
3. PLATING : GOLD PLATING OVER NICKEL.
4. OPERATING LIFE : 750 CYCLES MIN.
5. PCB RETENTION PRE-SOLDER : 1 LB MIN.
6. PCB RETENTION POST-SOLDER: 10 LBS MIN.

ENVIRONMENTAL:

1. STORAGE TEMPERATURE : -40°C TO +85°C.
2. OPERATION TEMPERATURE: -40°C TO +85°C.
3. WAVE SOLDERING TEMPERATURE:255~265°C(5~10SECONDS)
4. ROHS COMPLIANT

PORTS	DIM "A" ± 0.20	DIM "B" ± 0.20	DIM "C" ± 0.15
2	31.24	13.97	25.40
4	59.18	41.91	53.34
6	87.12	69.85	81.28
8	115.06	97.79	109.22
5	73.15	55.88	67.31

PART NUMBER	PORTS	CONTACT	GOLD PLATING
E5601-4EC362-L	4	10	6u"
E5608-4EC362-L	4	8	6u"
E5608-4EC364-L	4	8	15u"

DETACHED LISTS	MM (INCH)	RoHS Compliant				
	TOLERANCES EXCEPT AS NOTED		TITLE 11.5 SIDE ENTRY PCB GANG JACK 10P			
	MM					
.0 ± 0.2	±					
.00 ± 0.15	±					
.000 ± 0.075	±					
ANGLES ± 0.5						
THIRD ANGLE PROJECTION		DFTO Cothy	DRAWING NO. CE563060-LA		SIZE REV	
		DATE 2006/09/15	/PART NO. SEE TABLE		A3 0	
		SCALE : 1.25:1		DO NOT SCALE DRAWING	SHEET 1 OF 1	