

Direct Link

- Cross reference
- RoHS/LF P/N Search
- Customer drawing search
- 3D model search
- Industry Standards

Services

- E-Services
- Distributor list
- Price request
- Order samples


Documentation

- Free search
- Search by category

Start > Search=50006-1195C* > 50006-1195C

50006-1195C

50006-1195C - HPC : Header, Vertical 3 Row 0 Guides, Solder-less Press-Fit, 195 Positions



ACTIVE

Electronics division

[Print Datasheet](#)

FCI Brings You More

- [Contact our sales/technical support](#)
- [Sample request](#)
- [Price request](#)
- [Check distributor stock](#)

Customer Drawing

Specifications | **Download document** | **Mating Half**

General		Dimensional	Mounting	Physical
General				
Configuration	3 Rows with 0 Guide pins			
Contact type	Signal			
Keying Style	Yes			
Product Type	Vertical Header			
Shielded	No			
Number of Lines	195			
Number of power ports	0			
Number of signal pin fields	1			
Dimensional				
Length (Tail)	13.54 mm (0.533 in.)			
Mounting				
Board attachment	Press-Fit			
Physical				
Plating (Contact area)	0.76 µm (30 µin.) Gold 0.76 µm (30 µin.) GXT™ 1.27 µm (50 µin.) Gold			
Plating (Tail)	0.76 µm (30 µin.) GXT™ 0.76 µm (30 µin.) Gold 1.27 µm (50 µin.) Gold			