

SPECIFICATIONS

Mechanical

Contact Retention Force: 1.80kgf min.
Mating force: 340gf max. per contact pair
Unmating force: 28gf min. per contact pair
Durability: 500 Cycles

EW Series


R/A Type Brown, W/O Latches
2.54mm [.100"] Pitch
34 Pos.

Electrical


Current Rating: 3A max.
Current Voltage: 250V
Contact Resistance: 15mΩ max. initial
Dielectric Withstanding Voltage: 1000V
Insulation Resistance: 5000MΩ min.

Physical

Housing: Thermoplastic, UL 94V-0 rated, in Brown Color
Latch: Thermoplastic, UL 94V-0 rated, in Brown Color
Contact: Copper alloy
Plating: See "ORDERING INFORMATION"
Operating Temperature: -55°C to +85°C



DRAWING



ORDERING INFORMATION

PRDUCT NO: EW 1 17 0 * - TSR - DF

Series Prefix: _____
 2.54 mm Pitch
 Edge Card Conn.

Termination Type: _____
 1: Right Angle Type

No. of Pos.: _____
 17: 34 Pos.

Tail Length Type: _____
 0: 3.18mm

Plating Type: _____
 DF: Lead Free

Extension Code: _____

Gold Plating: _____
 1: Gold Flash
 3: 30u" Gold
 7: 15u" Gold