

DIMENSIONS ARE IN INCHES		UNLESS OTHERWISE NOTED		TOLERANCES ARE:		TITLE:	ASSEMBLY, SOCKET STRIP .016 X .031 TAIL [.41] [.79]	DWG NO:	SSW-1XX-XX-XXX-X-XX-XX-XX SHEET 1 OF 2
ONE PLACE DECIMALS ±	THREE PLACE DECIMALS ± .005 [.13]	ANGLES	± 2°	TWO PLACE DECIMALS ± .01 [.25]	FOUR PLACE DECIMALS ±				

TABLE 1
CONTACT SPECIFICATION

-XX	-S, -D, -T, -P	-S-RA, -P-RA	-D-RA	-T-RA
-01	C-8-1-X	N/A	N/A	N/A
-02	C-8-2-X	C-8-2-X	C-8-2-X C-8-3-X	C-8-2-X C-8-3-X C-8-5-X
-03	C-8-3-X	C-8-3-X	C-8-3-X C-8-5-X	N/A
-04	C-08-5-X	C-08-5-X	N/A	N/A
-06	C-8-6-X	N/A	N/A	N/A
-21	C-17-1-X	N/A	N/A	N/A
-22	C-17-2-X	C-17-2-X	C-17-2-X C-17-3-X	C-17-2-X C-17-3-X C-17-5-X
-23	C-17-3-X	C-17-3-X	C-17-3-X	N/A
-24	C-17-5-X	C-17-5-X	N/A	N/A

SSW-1XX-XX-XXX-X-XX-XX-XX

BODY LENGTH SPEC
-01 THRU -50
(-P OPTION: 36 POS MAX.)

CONTACT SPECIFICATION
(SEE TABLE 1)
-01 THRU -06 (STD. INS. FORCE)
-21 THRU -24 (LOW INS. FORCE)



PLATING SPECIFICATION
-G: GOLD- SPECIFY -G IN CONTACT SUFFIX -X
-T: TIN- SPECIFY -T IN CONTACT SUFFIX -X
(CONTACT -21 THRU -24 N/A)
-S: SELECTIVE- SPECIFY -S IN CONTACT SUFFIX -X
-H: HEAVY- SPECIFY -H IN CONTACT SUFFIX -X
-E: EXTRA HEAVY- SPECIFY -E IN CONTACT SUFFIX -X
(CONTACT -01 & -02 STRAIGHT ONLY)
-F: FLASH SELECTIVE- SPECIFY -F IN CONTACT SUFFIX -X
-P: GOLD FLASHED PALLADIUM NICKEL- SPECIFY -P IN CONTACT SUFFIX -X
-STL: SELECTIVE TIN/LEAD- SPECIFY -STL IN TERMINAL SUFFIX -XX
-TL: TIN/LEAD- SPECIFY -TL IN TERMINAL SUFFIX -X
(AVAILABLE ONLY ON LEAD STYLES -01.)
-TM: MATTE TIN SPECIFY -T IN TERMINAL SUFFIX -X
(CONTACT -21 THRU -24 N/A)
-SM: HEAVY GOLD SELECTIVE, MATTE TIN TAIL
SPECIFY -S IN TERMINAL SUFFIX -X
-FM: FLASH GOLD SELECTIVE, MATTE TIN TAIL
SPECIFY -F IN TERMINAL SUFFIX -X

OPTION
-LL: LOCKING LEAD
(SEE SHEET 2)
(N/A IN SINGLE ROW,
1 & 2 POSITION)

POLARIZING OPTION
INDICATE POS- SEE FIG. 3

OPTION
-RA: RIGHT ANGLE (SEE FIG. 1)
(CONTACT -01 & -21 N/A)

BODY SPECIFICATION
-S: USE SSW-XX-S
-D: USE SSW-XX-D
-T: USE SSW-50-T
-P: USE SSW-36-P
-Q: USE SSW-50-T (TRIPLE ROW
WITH ONLY 2 OUTER ROWS FILLED)



	IN-PROCESS	"D"	"E"	"F"
SSW-1XX-02-X-D-RA	.194 [4.93]	.394 [10.01]	-----	-----
SSW-1XX-03-X-D-RA	.394 [10.01]	.594 [15.09]	-----	-----
SSW-1XX-02-X-T-RA	.194 [4.93]	.394 [10.01]	.594 [15.09]	-----

TABLE 2

CONTACT	"B"	"C" REF			
	-S(-RA), -D, -T	-S-RA	-D-RA	-T-RA	
-01, -21	.104 [2.64]	N/A	N/A	N/A	
-02, -22	.194 [4.93]	.100 [2.54]	.100 [2.54]	.100 [2.54]	
-03, -23	.394 [10.01]	.300 [7.62]	.300 [7.62]	N/A	
-04, -24	.584 [14.83]	.490 [12.45]	N/A	N/A	
-06	.124 [3.15]	N/A	N/A	N/A	

PROPRIETARY NOTE
THIS DOCUMENT CONTAINS INFORMATION CONFIDENTIAL AND PROPRIETARY TO SAMTEC INC. AND SHALL NOT BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING, RECORDING, OR BY ANY INFORMATION STORAGE AND RETRIEVAL SYSTEM, WITHOUT THE WRITTEN CONSENT OF SAMTEC INC.

MATERIAL:
INSULATORS:
FLAMMABILITY RATING UL94 V-0
SINGLE
PRIMARY MATERIAL: VECTRA E130
ALTERNATE MATERIAL: VECTRA LCP 335
COLOR: BLACK
DOUBLE
PRIMARY MATERIAL: VECTRA E130
ALTERNATE MATERIAL: ZENITE 6130
COLOR: BLACK

TRIPLE ROW
MATERIAL: THERM-X CG907
COLOR: BLACK

TERMINAL:
PHOSPHOR BRONZE, SPRING TEMPER,
ALLOY 511 OR 510
(TENSILE STRENGTH 90-100 KSI)
(YIELD STRENGTH @ 2% OFFSET
88-98 KSI) PER MIL-B-13501
THICKNESS: .0250±.001 [.635±.03]

EXSPROD ASSEMBLY 1100
SSW-ASM

520 PARK EAST BLVD. NEW ALBANY, INDIANA 47150
PHONE (812) 944-6733 P.O. BOX 1147
CODE 55322

MADE BY: PURVIS 6-12-87



SSW-1XX-XX-XXX-X-XX-XX-XX
SHEET 1 OF 2

LOCKING LEAD OPTION



DIMENSIONS ARE IN INCHES		TOLERANCES ARE:	
ONE PLACE DECIMALS ±	THREE PLACE DECIMALS ± .010 [.25]	TWO PLACE DECIMALS ±	FOUR PLACE DECIMALS ± .0050 [.127]
		ANGLES ± 2°	

TITLE: ASSEMBLY, SOCKET STRIP
.016 X .031 TAIL
[.41] [.79]

DWG NO: SSW-1XX-XX-X-X-XX-XX-XX
SHEET 2 OF 2



CRIMP LOCATION (STRAIGHT & RA VERSIONS)



NOTE: LEAD STYLE X2-RA TO BE LAYER PACKAGED.




FIG. 3 POLARIZATION LOCATION
INSERT PK-06-N INTO SPECIFIED POS AND BREAK OFF TAB

PART #	TUBE	PLUG
-03/-23-S-RA SINGLE-RIGHT ANGLE	PT-3-24-01-01	TP-03
-04/24-S-RA SINGLE-RIGHT ANGLE	PT-1-24-01-34	TP-03
-03/-04/ -23-D-RA DOUBLE-RIGHT ANGLE	ASP-90341-01-S	TP-07
DELETED SSW T-RA & SSW Q-RA	PT-1-24-04-40	TP-07

PROPRIETARY NOTE
THIS DOCUMENT CONTAINS INFORMATION CONFIDENTIAL AND PROPRIETARY TO SAMTEC INC. AND SHALL NOT BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING, RECORDING, OR BY ANY INFORMATION STORAGE AND RETRIEVAL SYSTEM, WITHOUT THE WRITTEN CONSENT OF SAMTEC INC.

samtec MISC/MKTG SSW-MKTZ
520 PARK EAST BLVD. NEW ALBANY, INDIANA 47150
PHONE (812) 944-6733 P.O. BOX 1147
CODE 55322
MADE BY: PURVIS 6-12-87
SSW-1XX-XX-X-X-XX-XX-XX SHEET 2 OF 2