









Number of contacts

6-64



Female connector

Identification	No. of contacts	Part No.		Drawing	Dimensions in mm																																				
Female connector with central polarization		open end cover	closed end cover	open end cover	closed end cover																																				
	without strain relief clamp																																								
				option																																					
																																									
					Strain relief clamp option																																				
																																									
																																									
	Female connector without central polarization		open end cover	closed end cover																																					
without strain relief clamp																																									
					Strain relief clamp option																																				
																																									
																																									
<table><tr><th>No. of contacts</th><th>6</th><th>10</th><th>14</th><th>16</th><th>20</th><th>26</th><th>34</th><th>40</th><th>50</th><th>60</th><th>64</th></tr><tr><td>A</td><td>12.2</td><td>17.3</td><td>22.4</td><td>24.9</td><td>30.0</td><td>37.6</td><td>47.8</td><td>55.4</td><td>68.1</td><td>80.8</td><td>85.9</td></tr><tr><td>B</td><td>5.08</td><td>10.16</td><td>15.24</td><td>17.78</td><td>22.86</td><td>30.48</td><td>40.64</td><td>48.26</td><td>60.96</td><td>73.66</td><td>78.74</td></tr></table>						No. of contacts	6	10	14	16	20	26	34	40	50	60	64	A	12.2	17.3	22.4	24.9	30.0	37.6	47.8	55.4	68.1	80.8	85.9	B	5.08	10.16	15.24	17.78	22.86	30.48	40.64	48.26	60.96	73.66	78.74
No. of contacts	6	10	14	16	20	26	34	40	50	60	64																														
A	12.2	17.3	22.4	24.9	30.0	37.6	47.8	55.4	68.1	80.8	85.9																														
B	5.08	10.16	15.24	17.78	22.86	30.48	40.64	48.26	60.96	73.66	78.74																														

For performance level 3 please specify digit
 For performance level 2 please specify digit
 > 0.76 µm Au (30 pinch) on request

[7]
[6]
[5]*

[7]*
[6]*
[5]*

1) Contact number 1
 2) Pitch tolerance: ± 0.1

* Not normally kept in stock