

# USB CONNECTOR・IEEE 1394 CONNECTOR RECTANGULAR CONNECTOR





SMK

## USB CONNECTOR



### USB CONNECTOR USB コネクタ


- Rating: 1A 30V DC
- Contact Resistance: 30mΩ max.
- Insertion Force: 35N max.
- Withdrawl Force: 10N min.



## SMART MEDIA CONNECTOR




CLE9022-01□□



### SMART MEDIA CONNECTOR SmartMediaコネクタ





- Rating: 0.5A 250V AC
- Contact Resistance: 100mΩ max.
- Insulation Resistance: 1000MΩ min. at 500V DC
- Withstanding Voltage: 500V AC for one minute

## IEEE 1394 4P CONNECTOR



### IEEE 1394 4P CONNECTOR IEEE 1394 4P コネクタ


- Rating: 0.5A 5V DC
- Contact Resistance: 20mΩ max.
- Insulation Resistance: 1000MΩ min. at 100V DC
- Withstanding Voltage: 100V AC for one minute



## DATA PORT CONNECTOR





CSS5012-0801



### DATA PORT CONNECTOR データポートコネクタ

- Rating: 0.5A 125V AC
- Contact Resistance: 30mΩ max.
- Insulation Resistance: 250MΩ min. at 100V DC
- Withstanding Voltage: 300V AC for one minute
- Operating Temperature: -20°C~+70°C

## HALF PITCH CONNECTOR



### HALF PITCH CONNECTOR ハーフピッチコネクタ (1.27mmピッチ)


- Rating: 1A
- Contact Resistance: 35mΩ max.
- Insulation Resistance: 500MΩ min. at 500V DC

| No. | Part No.     | A     | B     | C     |
|-----|--------------|-------|-------|-------|
| 26  | CSC9026-0101 | 31.26 | 20.30 | 15.24 |
| 50  | CSC9050-0101 | 46.50 | 35.50 | 30.48 |
| 100 | CSC9090-0201 | 78.25 | 67.30 | 62.23 |

## D-SUB CONNECTOR



CDC3125-02□□



### D-SUB CONNECTOR D-Subコネクタ


- Rating: 5A 300V DC
- Contact Resistance: 15mΩ max.
- Insulation Resistance: 1000MΩ min. at 500V DC
- Withstanding Voltage: 500V AC for one minute
- Operating Temperature: -55°C~+105°C

※各種レバトリリーを取揃えてありますので個別カタログをご請求ください。

## CENTRONICS CONNECTOR



CSC3150-01□□




### CENTRONICS CONNECTOR セントロニクス仕様コネクタ

- Rating: 5A 300V DC
- Contact Resistance: 25mΩ max.
- Insulation Resistance: 1000MΩ min. at 500V DC
- Withstanding Voltage: 1000V AC for one minute
- Operating Temperature: -55°C~+105°C

## ATAPI 5 in 1 CONNECTOR



CSC5055-0301



### ATAPI 5 in 1 CONNECTOR ATAPI 5 in 1 コネクタ

- Rating: 250V AC
- Contact Resistance: 30mΩ max.
- Insulation Resistance: 1000MΩ min. at 500V DC
- Withstanding Voltage: 1000V AC for one minute
- Operating Temperature: -40°C~+85°C