

DEVICE TYPE NO.	POLARITY	P _D @ T _C =25°C	MAXIMUM RATINGS				ELECTRICAL CHARACTERISTICS				CASE
		WATTS	I _C AMPS	BV _{CEO}	BV _{CE}	BV _{EBD}	h _{FE} MIN.	I _C AMPS	V _{CE}	f MHZ *KHZ	
2N6329	PNP	200	30.0	60	60	5	12	15.0	4	3	T03
2N6330	PNP	200	30.0	80	80	5	12	15.0	4	3	T03
2N6331	PNP	200	30.0	100	100	5	12	15.0	4	3	T03
2N6338	NPN	200	25.0	120	100	6	30	10.0	2	40	T03
2N6339	NPN	200	25.0	140	120	6	30	10.0	2	40	T03
2N6340	NPN	200	25.0	160	140	6	30	10.0	2	40	T03
2N6341	NPN	200	25.0	180	150	6	30	10.0	2	40	T03
2N6354	NPN	140	10.0	150	120	6.5	10	10.0	2	80	T03
2N6375	NPN	580	1.50	75	40	6	60	.010	1	300	T018
2N6376	NPN	250	50.0	160	140	6	30	20.0	4	30	T03
2N6383	NPN	100	10.0	40	40	5	1.0K	5.00	3	20	T03
2N6384	NPN	100	10.0	60	60	5	1.0K	5.00	3	20	T03
2N6385	NPN	100	10.0	80	80	5	1.0K	5.00	3	20	T03
2N6386	NPN	60.0	10.0	40	40	5	1.0K	5.00	3	20	T0220
2N6387	NPN	60.0	10.0	60	60	5	1.0K	5.00	3	20	T0220
2N6388	NPN	60.0	10.0	80	80	5	1.0K	5.00	3	20	T0220
2N6469	PNP	125	15.0	50	40	5	20	5.00	4	10	T03
2N6470	NPN	125	15.0	50	40	5	20	5.00	4	5	T03
2N6471	NPN	125	15.0	70	60	5	20	5.00	4	5	T03
2N6472	NPN	125	15.0	90	80	5	20	5.00	4	5	T03
2N6473	NPN	16.0	4.00	110	110	5	15	1.50	4	4	T0220
2N6474	NPN	16.0	4.00	130	130	5	15	1.50	4	4	T0220
2N6475	PNP	16.0	4.00	110	110	5	15	1.50	4	4	T0220
2N6476	PNP	16.0	4.00	130	130	5	15	1.50	4	4	T0220
2N6478	NPN	20.0	2.50	160	160	5	25	1.00	4	*200	T0220
2N6486	NPN	75.0	15.0	50	40	5	20	5.00	4	5	T0220
2N6487	NPN	75.0	15.0	70	60	5	20	5.00	4	5	T0220
2N6488	NPN	75.0	15.0	90	80	5	20	5.00	4	5	T0220
2N6489	PNP	75.0	15.0	50	40	5	20	5.00	4	5	T0220
2N6490	PNP	75.0	15.0	70	60	5	20	4.00	4	5	T0220
2N6491	PNP	30.0	15.0	90	90	5	20	4.00	4	5	T0220
2N6496	NPN	80.0	15.0	150	130	7	12	8.00	2	60	T03
2N6510	NPN	120	7.00	250	200	6	10	3.00	3	3	T03
2N6511	NPN	120	7.00	300	250	6	10	4.00	3	3	T03
2N6512	NPN	120	7.00	350	300	6	10	4.00	3	3	T03
2N6513	NPN	120	7.00	400	350	6	10	4.00	3	3	T03
2N6514	NPN	120	7.00	350	300	6	10	5.00	3	3	T03
2N6530	NPN	65.0	8.00	80	80	5	1000	5.00	3	20	T0220
2N6531	NPN	65.0	8.00	100	100	5	500	3.00	3	20	T0220
2N6532	NPN	65.0	8.00	100	100	5	1000	5.00	3	20	T0220
2N6533	NPN	65.0	8.00	120	120	5	1000	3.00	3	20	T0220
2N6542	NPN	100	5.00	650	300	8	12	1.50	2	6	T03
2N6543	NPN	100	5.00	850	400	8	12	1.50	2	6	T03
2N6544	NPN	125	8.00	650	300	9	12	2.50	3	6	T03
2N6545	NPN	125	8.00	850	400	9	12	2.50	3	6	T03
2N6546	NPN	175	15.0	650	300	9	12	5.00	2	6	T03
2N6547	NPN	175	15.0	850	400	9	12	5.00	2	6	T03
2N6569	NPN	100	12.0	45	40	5	15	4.00	3	1.5	T03
2N6576	NPN	120	15.0	60	60	7	2000	4.00	3	10	T03
2N6577	NPN	120	15.0	90	90	7	2000	4.00	3	10	T03
2N6578	NPN	120	15.0	120	120	7	2000	4.00	3	10	T03
2N6594	PNP	100	12.0	45	40	5	15	4.00	3	2.5	T03
2N6609	PNP	150	16.0	160	140	7	15	8.00	4	2	T03
2N6645	PNP	70.0	10.0	40	40	5	1000	5.00	3	20	T0220
2N6649	PNP	70.0	10.0	60	60	5	1000	5.00	3	20	T0220
2N6650	PNP	70.0	10.0	80	80	5	1000	5.00	3	20	T0220
2N6666	PNP	70.0	8.00	40	40	5	1000	3.00	3	20	T0220
2N6667	PNP	70.0	10.0	60	60	5	1000	5.00	3	20	T0220
2N6668	PNP	70.0	10.0	80	80	5	1000	5.00	3	20	T0220
2N6671	NPN	150	8.00	450	300	8	10	5.00	3	15	T03
2N6672	NPN	150	8.00	550	350	8	10	5.00	3	15	T03
2N6673	NPN	150	8.00	650	400	8	10	5.00	3	15	T03
2N6674	NPN	175	15.0	450	300	7	8	10.0	2	15	T03
2N6675	NPN	175	15.0	650	400	7	8	10.0	2	15	T03

