
**Pomona
ACCESS**


FAX ON DEMAND This symbol indicates immediate Fax-On-Demand Technical Information is available. Dial (U.S.) (800) 444-6785, (Outside U.S.) (909) 469-2991. Enter the Pomona Access number (shown in *italics*) when prompted.

ALLIGATOR TEST CLIP TO SHEATHED BANANA PLUG PATCH CORD
NEW


Alligator length: 2.3", jaw opening .300"
Wire: High flex 18 AWG Silicone wire
RATING: 150V, 5 Amps, +50°C (+122°F) Max.
STD COLORS: -0 blk, -2 red, -4 yellow, -5 green, -6 blue.

**Pomona
ACCESS**

Part No.	Length	PRICE
6489-48*	48"	4.50

EXTRA LARGE ALLIGATOR TEST CLIP TO SHEATHED BANANA PLUG PATCH CORD
NEW


Alligator length: 3.6", jaw opening: 0.8"
Conforms to IEC1010-2-031, Overvoltage Category III, 1000V, 10 Amps
Wire: High flex 18 AWG Silicone wire
STD COLORS: -0 blk, -2 red.

**Pomona
ACCESS**

Part No.	Length	PRICE
6570-36*	36"	12.00
6570-48*	48"	13.00

EXTRA LARGE ALLIGATOR TEST CLIP PATCH CORD
NEW


Alligator length: 3.6", jaw opening: 0.8"
Conforms to IEC1010-2-031, Overvoltage Category III, 1000V, 10 Amps
Wire: High flex 18 AWG Silicone wire
STD COLORS: -0 blk, -2 red.

**Pomona
ACCESS**

Part No.	Length	PRICE
6569-36*	36"	14.00
6569-60*	48"	15.00


RETRACTABLE SHEATH STACKING BANANA PLUG PATCH CORD


18 AWG wire, .144 O.D.
RATING: 1200V AC/DC Max., 7 Amps, +55°C (+131°F) Max.
*STD COLORS: -0 blk, -2 red.

**Pomona
ACCESS**

Part No.	Length	PRICE
5403-12*	12"	8.50
5403-24*	24"	8.50
5403-36*	36"	8.50
5403-48*	48"	8.95
5403-60*	60"	8.95

This retractable sheath banana plug has a stacking feature allowing the insertion of standard or other retractable plugs.

RETRACTABLE SHEATH BANANA PLUG PATCH CORD


18 AWG Wire, .144 O.D.
RATING: 1000V per IEC1010-2-031, 10 Amps, +80°C (+176°F) Max.
*STD COLORS: -0 blk, -2 red.

**Pomona
ACCESS**

Part No.	Length	PRICE
4911A-12*	12"	8.85
4911A-18*	18"	8.85
4911A-24*	24"	8.85
4911A-36*	36"	8.85
4911A-48*	48"	8.85
4911A-60*	60"	8.85

SMD GRABBER® TEST CLIP TO RETRACTABLE SHEATH BANANA PLUG PATCH CORD


Pincer opens to .090.
22 AWG Wire, .064 O.D.
RATING: 150V, 0.5 Amps, +55°C (+131°F) Max.
*STD COLORS: -0 blk, -2 red.

**Pomona
ACCESS**

Part No.	Length	PRICE
5362-36*	36"	8.80

MINIGRABBER® TEST CLIP TO RETRACTABLE SHEATH BANANA PLUG PATCH CORD


Features a slim (.36) body width. Hook attaches to component leads up to .060 O.D.
18 AWG Silicone insulated wire, .144 O.D.
RATING: 300V, 5 Amps per IEC1010-2-031
*STD. COLORS: -0 blk, -2 red.

**Pomona
ACCESS**


Part No.	Length	PRICE
6250A-12*	12"	6.70
6250A-24*	24"	6.70
6250A-36*	36"	6.70

MINIGRABBER® TEST CLIP TO RETRACTABLE SHEATH BANANA PLUG PATCH CORD


Hook attaches to component leads up to .060 O.D.
20 AWG Wire, .087 O.D.
RATING: 300V, 5 Amps, +55°C (+131°F) Max.
*STD COLORS: -0 blk, -2 red.

**Pomona
ACCESS**

Part No.	Length	PRICE
5270-12*	12"	6.30
5270-24*	24"	6.30
5270-36*	36"	6.30
5270-48*	48"	6.70
5270-60*	60"	6.70

MINIGRABBER® TEST CLIP TO STRAIGHT BANANA PLUG PATCH CORD


Features a slim (.36) body width. Hook attaches to component leads up to .060 O.D.
18 AWG Silicone insulated wire, .144 O.D.
RATING: 300V, 5 Amps
*STD. COLORS: -0 blk, -2 red.

**Pomona
ACCESS**

Part No.	Length	PRICE
6251-12*	12"	4.90
6251-24*	24"	4.90
6251-36*	36"	4.90

MINIGRABBER® TEST CLIP TO STRAIGHT BANANA PLUG PATCH CORD


Hook attaches to component leads up to .060 O.D.
20 AWG Wire, .087 O.D.
RATING: 300V, 5 Amps, +50°C (+122°F) Max.
*STD COLORS: -0 blk, -2 red.

**Pomona
ACCESS**

Part No.	Length	PRICE
4650-12*	12"	4.65
4650-24*	24"	4.65
4650-36*	36"	4.65
4650-48*	48"	4.90
4650-60*	60"	4.90