

EC CONNECTORS

PF0030/28

-
- | List No. | DIM A |
|------------|-------|
| PF0030/28. | 38.0 |
| PF0030/48. | 38.0 |
| PF0030/63. | 40.0 |

PF0030/PC

-
- Technical drawings of the Panel Fixing Details. The drawings include a top view, a side view, and a detail view of the P.C.B. Fixing Details. Dimensions are given in millimeters.
- Top View:**
- Overall width: 44.0
 - Overall height: 40.0
 - Panel width: 36.00
 - Panel height: 31.3 Min
 - Panel mounting hole diameter: Ø3.4
 - Panel mounting hole spacing: 28.1 Min
- Side View:**
- Panel thickness: 2.0
 - Mounting height: 4.0
 - Mounting hole diameter: Ø3.4
 - Mounting hole spacing: 19.5
 - Mounting hole diameter: Ø1.70
 - Mounting hole spacing: 11.70 CRS
- P.C.B. Fixing Details:**
- Mounting hole diameter: Ø3.40 x 2 OFF
 - Mounting hole spacing: 12.00
 - Mounting hole diameter: Ø1.70
 - Mounting hole spacing: 11.70 CRS
 - Mounting hole diameter: Ø1.70
 - Mounting hole spacing: 14.00 CRS

PF0033/10/28

-
- Technical drawing of the PF0033/10 series pressure washer, showing front, side, and top views with dimensions.
- Front View:** Shows a square body with a width of 31.0 and a height of 34.1. The internal components, including the trigger gun and spray lance, are visible.
- Side View:** Shows the side profile of the device. The trigger gun and spray lance are shown in the retracted position. The width of the trigger gun is 2.0, and the width of the spray lance is 4.0. The overall width of the device is 27.3 Min. The height of the device is 31.1 Min. The dimension line for the overall width is labeled DIM A.
- Top View:** Shows the top of the device, which is a square with a side length of 27.3 Min. The dimension line for the overall width is labeled DIM A.
- Fixing Details:** The text "Fixing Details" is written below the top view, indicating the mounting points for the device.
- List No. DIM A**
- | | |
|---------------|------|
| PF0033/10/28. | 38.0 |
| PF0033/10/48. | 39.0 |
| PF0033/10/63. | 40.0 |

RoHS