




.050 [1.27] Pitch Image Sensor DIP Sockets

Top View Shown

Units: in [mm]

Fig.8



For Terminal Details or other
Terminal Types see Page 20

- 274 Terminal
Shown


Andon Part Number w/Thru-Hole Terminal	Surface Mount Terminal	Figure Number	Pin QTY.	A	B	C	D
IS232-316-274U-R27-L14	281U	8	16	.300 (7.62)	.350 (8.89)	.385 (9.78)	.447 (11.35)
IS232-414-274U-R27-L14	281U	8	14	.400 (10.16)	.300 (7.62)	.485 (12.32)	.397 (10.08)
IS232-416-274U-R27-L14	281U	8	16	.400 (10.16)	.350 (8.89)	.485 (12.32)	.447 (11.35)
IS232-440-274U-R27-L14	281U	8	40	.400 (10.16)	.950 (24.13)	.485 (12.32)	1.047 (26.59)
IS232-4516-274U-R27-L14	281U	8	16	.450 (11.43)	.350 (8.89)	.535 (13.59)	.447 (11.35)
IS232-4820-274U-R27-L14	281U	8	20	.480 (12.19)	.450 (11.43)	.565 (14.35)	.547 (13.89)
IS232-520-274U-R27-L14	281U	8	20	.500 (12.70)	.450 (11.43)	.585 (14.86)	.547 (13.89)
IS232-522-274U-R27-L14	281U	8	22	.500 (12.70)	.500 (12.70)	.585 (14.86)	.597 (15.16)
IS232-5724-274U-R27-L14	281U	8	24	.570 (14.48)	.550 (13.97)	.655 (16.64)	.647 (16.43)
IS232-622-274U-R27-L14	281U	8	22	.600 (15.24)	.500 (12.70)	.685 (17.40)	.597 (15.16)
IS232-628-274U-R27-L14	281U	8	28	.600 (15.24)	.650 (16.51)	.685 (17.40)	.747 (18.97)

.050 [1.27] Pitch Image Sensor SIP Sockets

Top View Shown

Units: in [mm]

Fig.13



Andon Part Number w/Thru-Hole Terminal	Surface Mount Terminal	Figure Number	Pin QTY.	B	C	D
417-05-274U-R27-L14	281U	13	5	.200 (5.08)	.085 (4.80)	.297 (7.54)
417-06-274U-R27-L14	281U	13	6	.250 (6.35)	.085 (4.80)	.347 (8.81)
417-07-274U-R27-L14	281U	13	7	.300 (7.62)	.085 (4.80)	.397 (10.08)
417-08-274U-R27-L14	281U	13	8	.350 (8.89)	.085 (4.80)	.447 (11.35)
417-09-274U-R27-L14	281U	13	9	.400 (10.16)	.085 (4.80)	.497 (12.62)
417-10-274U-R27-L14	281U	13	10	.450 (11.43)	.085 (4.80)	.547 (13.89)
417-11-274U-R27-L14	281U	13	11	.500 (12.70)	.085 (4.80)	.597 (15.16)
417-12-274U-R27-L14	281U	13	12	.550 (13.97)	.085 (4.80)	.647 (16.43)
417-13-274U-R27-L14	281U	13	13	.600 (15.24)	.085 (4.80)	.697 (17.70)
417-14-274U-R27-L14	281U	13	14	.650 (16.51)	.085 (4.80)	.747 (18.97)
417-15-274U-R27-L14	281U	13	15	.700 (17.78)	.085 (4.80)	.797 (20.24)
417-16-274U-R27-L14	281U	13	16	.750 (19.05)	.085 (4.80)	.847 (21.51)
417-17-274U-R27-L14	281U	13	17	.800 (20.32)	.085 (4.80)	.897 (22.78)
417-18-274U-R27-L14	281U	13	18	.850 (21.59)	.085 (4.80)	.947 (24.05)
417-19-274U-R27-L14	281U	13	19	.900 (22.86)	.085 (4.80)	.997 (25.32)
417-20-274U-R27-L14	281U	13	20	.950 (24.13)	.085 (4.80)	1.047 (26.59)
417-21-274U-R27-L14	281U	13	21	1.000 (25.40)	.085 (4.80)	1.097 (27.86)
417-22-274U-R27-L14	281U	13	22	1.050 (26.67)	.085 (4.80)	1.147 (29.13)
417-23-274U-R27-L14	281U	13	23	1.100 (27.94)	.085 (4.80)	1.197 (30.40)
417-24-274U-R27-L14	281U	13	24	1.150 (29.21)	.085 (4.80)	1.247 (31.67)
417-25-274U-R27-L14	281U	13	25	1.200 (30.48)	.085 (4.80)	1.297 (32.94)
417-26-274U-R27-L14	281U	13	26	1.250 (31.75)	.085 (4.80)	1.347 (34.21)
417-27-274U-R27-L14	281U	13	27	1.300 (33.02)	.085 (4.80)	1.397 (35.48)
417-28-274U-R27-L14	281U	13	28	1.350 (34.29)	.085 (4.80)	1.447 (36.75)
417-29-274U-R27-L14	281U	13	29	1.400 (35.56)	.085 (4.80)	1.497 (38.02)
417-30-274U-R27-L14	281U	13	30	1.450 (36.83)	.085 (4.80)	1.547 (39.29)

For Other Pin Configuration or Layouts, Contact Factory.

RoHS Compliant

Andon Proprietary Information

IS-09B 11/3/09

©Copyright 2009 Andon Electronics Corporation. All Rights Reserved. This material is protected under US and other copyrights and may not be copied, sold, or redistributed in any form without written permission of Andon Electronics Corporation. Copyrights and trademarks are property of their respective companies. We reserve the right to change specifications without notice. Andon makes no warranty, expressed or implied, as to the suitability of the sockets for the intended purpose.

ANDON ELECTRONICS CORPORATION
4 Court Drive, Lincoln RI 02865, United States of America

www.andonelectronics.com or www.andonelect.com
Phone 401-333-0388 Fax 401-333-0287
Email Info@andonelect.com