

Copper cables

- Cat.5
- in PUR or PVC







Cable by the metre

4-core cables for connecting M12 plug-in connectors, d-coded; assemble your 4-core cable exactly at the place of use $\,$

- Installation cable in PVC
- Connecting cable in PVC
- Moving carrier cable in PUR (halogen-free)

Pre-assembled

4-core cables, assembled at both ends with M12 plugs, d-coded

- Suitable for moving cable carriers
- IP67
- In PUR
- Halogen-free
- Wear-resistant and very robust
- Plug-and-play

Technical data

Category
Cross-section, solid
Cross-section, flexible
Wire insulation diameter
Cladding material
Sheathing colour
Cladding diameter
Operating temperature

| Cat.5 | |
|------------------|--|
| 2 x 2 x AWG22/1 | |
| 2 x 2 x AWG22/7 | |
| 1.5 mm | |
| PVC or PUR | |
| green (RAL 6018) | |
| 6.3 6.7 mm | |
| –40 °C +70 °C | |
| | |
| | |
| | |
| | |
| | |
| | |

Ordering data

Installation cable, solid Connecting cable, 7 strands Moving carrier cable, 7 strands

Pre-assembled, 1.5 m M12-M12 Pre-assembled, 3 m M12-M12 Pre-assembled, 5 m M12-M12 Pre-assembled, 10 m M12-M12

| IE-C5AS4V1000 | 889900000 |
|------------------------|------------|
| IE-C5DS4V1000 | 8898990000 |
| IE-C5DD4U1000 | 8899010000 |
| | |
| IE-C5DD4UG0015MCSMCS-X | 8877610015 |
| IE-C5DD4UG0030MCSMCS-X | 8877610030 |
| IE-C5DD4UG0050MCSMCS-X | 8877610050 |
| IE-C5DD4UG0100MCSMCS-X | 8877610100 |
| | |
| | |
| | |
| | |
| | |
| | |

Order No.

Note

Accessories

Conductor markers Conductor markers Sheathing stripper Marking plate

| r | V | C | 1 | Ţ | 3 |
|---|---|---|---|---|---|
| | | | | | |
| | | | | | |

| Туре | Order No. |
|-------------|------------|
| SF 5/21 | 1689470001 |
| SF 6/21 | 1730560001 |
| CST | 9204350000 |
| TM18, white | 1718431044 |
| | |

Туре