
Ditouch Connectors CAM-C73 · C74 Series

Connectors

FEATURES

- Due to these connectors, the front panel can be removed or mounted for preventing the car audio from being stolen.
- 2. The socket has a coupling position guide to absorb play when coupled.
- 3. A metallic cover is mounted for preventing static electricity.



HOW TO ORDER

1.CAM-C73 (Plug)

 $\frac{\text{C73}}{1} - \frac{\text{O16}}{2} - \frac{\text{O2}}{3} + \frac{\text{B}}{4} + \frac{\text{G}}{5} + \frac{\text{G}}{6} + \frac{\text{A}}{7} + \frac{\text{A}}{8} + \frac{\text{A}}{9}$

1 Series No. (C73)

2 No. of contacts (016: 16pins)

3 Housing material (02: PBT resin)

4 UL grade of housing (0: UL94V-0)

- 5 Contact finish of contact pins and lead pins (B : Contacts area Gold plating, Leads area Solder plating)
- 6 Contact plating thickness (G: 0.3µ)
- 7 Contact pin lead style (G: Angle SMT)
- 8 Accesory for connector outside (A : None)
- 9 Accesory for connector inside (A : None)

2.CAM-C74 (Socket)

 $\frac{\mathbf{C74}}{1} - \frac{\mathbf{016}}{2} - \frac{\mathbf{02}}{3} \quad \frac{\mathbf{0}}{4} - \frac{\mathbf{B}}{5} \quad \frac{\mathbf{G}}{6} \quad \frac{\mathbf{G}}{7} \quad \frac{\mathbf{A}}{8} \quad \frac{\mathbf{A}}{9}$

1 Series No. (C74)

2 No. of contacts (016: 16pins)

3 Housing material (02: PBT resin)

4 UL grade of housing (0: UL94V-0)

5 Contact finish of contact pins and lead pins (B: Contacts area Gold plating, Leads area Solder plating)

6 Contact plating thickness (G: 0.3µ)

7 Contact pin lead style (B : Angle SMT)

8 Accesory for connector outside (A : None)

9 Accesory for connector inside (A : None)

SPECIFICATIONS

ELECTRICAL CHARACTERISTICS

Rated Voltage	14V DC
Rated Current	1A
Withstanding Voltage	500V AC (rms) 1minute
Insulation Resistance	100MΩ min. (at 500V DC)
Contact Resistance	70mΩ max.

MECHANICAL CHARACTERISTICS

Life (Mating cycle)	10,000times
Total Insertion Force	14.7N (1~5kgf) max.
Using Temperature Range	-30~+85°C
Overall Rebound Force	8.18N (0.835kgf) max.

MATERIAL & FINISH

	Component parts	Material	Finish
CAM-C73	Housing	PBT resin	
Series	Contact	Copper Alloy	Gold selective plating
	Housing	PBT resin	
CAM-C74 Series	Contact	Copper Alloy	Gold selective plating
	Cover	Copper Alloy	Brack nickel plating, Tin reflow plating

CAM-C74 Series

22±0.1

Boss pitch size

DIMENSIONS

Both pitch size

CAM-C73 Series

Unit : mm