

14 Pin DIP Package

HTFLxx Series HTVLxx Series

HTFHxx Series HTVHxx Series

CONNOR WINFIELD



TCXO / VCTCXO

2111 Comprehensive Drive

Aurora, Illinois 60505

Phone: 630-851-4722

Fax: 630-851-5040

www.conwin.com

US Headquarters:



630-851-4722

European Headquarters:

+353-61-472221

Description

The Connor Winfield 14 Pin DIP Temperature Compensated Crystal Controlled Oscillators (TCXO series) and Voltage Controlled Temperature Compensated Crystal Controlled Oscillators (VCTCXO series) are designed for use in applications where high frequency stability performance is required. Through the use of Analog Temperature Compensation this device is capable of holding sub 1-ppm stabilities over the commercial or the industrial temperature ranges. Many features are available to meet your design requirements.



Features:

- Available RoHS Options:
RoHS Compliant / Lead Free
RoHS Compliant / Terminations Contain Lead
- Fixed Frequency with Tri-State E/D (TCXO) or Voltage Controlled (VCTCXO)
- Available Supply Voltages: 3.3v or 5.0v
- Low Jitter >1ps Rms
- Available Frequency Stabilities:
6.4 Mhz to 52 Mhz, 0.28 ppm pk-pk, ±0.20 ppm, ±0.25 ppm, ±0.28 ppm, ±0.50 ppm, ±1.00 ppm, ±2.50 ppm, ±4.60 ppm
- Available Temperature Ranges:
0 to 70°C or -40 To 85°C
- Tri-State Enable / Disable Function or Voltage Control Pin 1
- Hermetically Sealed 14 Pin Dip Package

Absolute Maximum Ratings

Table 1.0

Parameter	Minimum	Nominal	Maximum	Units	Notes
Storage Temperature	-55	-	125	°C	
Supply Voltage (Vcc)	-0.5	-	6.0	Vdc	
Input Voltage (Vcc)	-0.5	-	Vcc+0.6	Vdc	



Ordering Information

HTFL6D - 12.800 MHz

TCXO
SERIES

CENTER
FREQUENCY

Bulletin	Tx137
Page	1 of 4
Revision	06
Date	27 Jan 2009



Operating Specifications

Table 2.0

Parameter	Minimum	Nominal	Maximum	Units	Notes
Center Freq (See Table 8) (Fo)	6.40	-	52	MHz	
Frequency Calibration – All Models	-1.0		1.0	ppm	1
Frequency Stability vs. Temperature $\pm[(F_{max}-F_{min})/2]$ (See Table 8)					2
Freq. Stability vs. Voltage - All Models	-	-	± 0.20	ppm	3
Total Frequency Tolerance – HTxxxA through HTxxxF	-	-	± 4.6	ppm	4
Total Frequency Tolerance – HTxxxG	-	-	± 6.1	ppm	4
Total Frequency Tolerance – HTxxxH	-	-	± 20.0	ppm	4
Aging (20 years) – All Models	-	-	± 3.0	ppm	
Operating Temperature Range (See Table 8)					
Model: HTxx5x- Series	0	-	70	°C	
Model: HTxx6x- Series	-40	-	85	°C	
Supply Voltage (See Table 7)					
Model: HTFLxx or HTVLxx - Series (Vcc)	3.135	3.300	3.465	Vdc	
Model: HTFHxx or HTVHxx - Series (Vcc)	4.75	5.00	5.25	Vdc	
Supply Current (6.4 to 52 MHz) (Icc)	-	6	10	mA	
Phase Jitter (BW = 12KHz to Fo/2)	-	-	1	pS RMS	
Phase Jitter (BW = 10Hz to Fo/2)	-	-	3	pS RMS	
Period Jitter	-	-	3	pS RMS	
SSB Phase Noise at 1Hz offset	-	-50	-	dBc/Hz	
SSB Phase Noise at 10 Hz offset	-	-80	-	dBc/Hz	
SSB Phase Noise at 100 Hz offset	-	-110	-	dBc/Hz	
SSB Phase Noise at 1 KHz offset	-	-135	-	dBc/Hz	
SSB Phase Noise at 10K Hz offset	-	-150	-	dBc/Hz	
SSB Phase Noise at 100 KHz offset	-	-150	-	dBc/Hz	
Start-Up Time: Oscillator	-	-	10	mS	
TDEV @ 1 second	-	-	1.0	nS	
TDEV @ 4 seconds	-	-	2.0	nS	

Notes:

- 1) Initial calibration @ 25°C. Specifications at time of shipment after 48 hours of operation.
- 2) Frequency stability vs. change in temperature. $\pm[(F_{max}-F_{min})/2]$, where the Fmax and Fmin values are in ppm.
- 3) Frequency stability for a +/- 5% supply voltage change.
- 4) Inclusive of calibration, operating temperature range, supply voltage change, shock and vibration and aging (20 years).
- 5) Oscillator output is enabled with no connection on pin 1. Output is at high impedance when disabled.

Input Characteristics for VCTCXO Models

Table 3.0

Parameter	Minimum	Nominal	Maximum	Units	Notes
Control Voltage Range (Vcc = 3.3V) (Vc)	0.3	1.65	3.0	Vdc	
Control Voltage Range (Vcc = 5.0V) (Vc)	0.5	2.5	4.5	Vdc	
Frequency Tuning	± 10	-	-	ppm	
Linearity	± 1	-	-	%	
Slope	Positive				
Input Resistance	>100K	-	-	Ohm	

Input Characteristics for TCXO Models

Table 4.0

Parameter	Minimum	Nominal	Maximum	Units	Notes
Enable Voltage (High) (Vih)	$\geq 70\% V_{dd}$	-	-	Vdc	5
Disable Voltage (Low) (Vil)	-	-	$\leq 30\% V_{dd}$	Vdc	5



CMOS Output Characteristics

Table 5.0

Parameter	Minimum	Nominal	Maximum	Units	Notes
LOAD	-	15	-	pF	1
Output Voltage 6.4 to 52 MHz					
Voltage: (High) (Voh)	90%Vcc	-	-	V	
(Low) (Vol)	-	-	10%Vcc	V	
Drive Current for 6.4 to 52 MHz					
(High) (Ioh)	-4	-	-	mA	
(Low) (Iol)	-	-	4	mA	
Duty Cycle at 50% of Vcc	45	50	55	%	
Rise / Fall Time 10% to 90%	-	-	8	nS	

1) For best performance it is recommended that the device connected to this output should have an equivalent input capacitance of 15pF.

Package Characteristics

Table 6.0

Package	Hermetically sealed, 14 Pin DIP metal package
---------	---

Process Recommendation

Solder Reflow Products suitable for convection reflow soldering. Peak temperature 260°C.
Maximum time above 220°C, 20 seconds

Model Number Select Table

Table 7.0

Fixed Frequency Models	Voltage Controlled Models	Supply Voltage	Output Logic Type
HTFLxx	HTVLxx	3.3 Vdc	HCMOS
HTFHxx	HTVHxx	5.0 Vdc	HCMOS

xx — Add the frequency vs. temperature range to the end of the model number.

Frequency vs. Temperature Range

Table 8.0

Select Table Frequency Range: 6.4 to 52 MHz

Operating Temperature Ranges	0.28 ppm pk-pk*	±0.20 ppm***	±0.25 ppm***	±0.28 ppm***	±0.50 ppm***	±1.00 ppm***	±2.50 ppm***	±4.60 ppm***
0 to 70°C	5A	5B	5C	5D	5E	5F	5G	5H
-40 to 85°C	**	**	**	6D	6E	6F	6G	6H

* — Frequency vs. temperature, absolute.

** — Frequency stabilities not available at -40 to 85°C

*** — $\pm[(F_{max}-F_{min})/2]$, where the F_{max} and F_{min} values are in ppm.



Package Dimensions






Table 9.0

Pin Function	
1	E / D or Voltage Control
7	Ground
8	Output
14	Vcc


RoHS 5/6 Solder Profile



Phase Noise Plot



RoHS Solder Profile



Order Information Specifications


HTVH 5D G5 - 020.0M

Model Number, Fixed or Voltage Controlled Output, Supply Voltage - Code
 Frequency Stability vs. Temperature Range - Code
 G5 = RoHS 5/6 Compliant / Terminations Contain Lead
 Blank = RoHS Compliant / Lead Free
 Output Frequency

HTVH5DG5-020.0M = 20 MHz MHz, Voltage Controlled VCTCXO, 5.0V, HCMOS, ±0.28ppm, 0 to 70°C, RoHS 5/6 Compliant / Terminations contain lead.

HTFL6D-012.8M = 12.8 MHz, Fixed Frequency TCXO, 3.3V, HCMOS, ±0.28ppm, -40 to 85°C, RoHS Compliant / Lead Free

Output Waveform



Test Circuit

