

Part/Keyword Search



Detailed Drawing



Printer Friendly
Datasheet

PN7104 / SPN7104*


* Part number for additional environmental screening.

Performance Data


Frequency	5.0 - 150.0 MHz
Gain	24.0 dB Typical 22.5 dB Min
Noise Figure	1.9 dB Typical 2.5 dB Max
P _{1dB}	12.0 dBm Typical 10.5 dBm Min
3 rd Order Intercept	25.0 dBm Typical
2 nd Order Intercept	31.0 dBm Typical
VSWR	1.8/2.0 Input Typ/Max 1.8/2.0 Output Typ/Max
Reverse Isolation	-27.0 dB Typical -26.0 dB Min
Power Supply	5.0 Volts 20.0 mA
Operating Temperature	-55.0 - 85.0 °C

Package Drawing


SM-11 (Surface Mount)



Gain




Noise Figure




Frequency (MHz)

P_{1dB} Compression Point




Frequency (MHz)

Reverse Isolation




Frequency (MHz)

Input VSWR



Frequency (MHz)

Output VSWR



Frequency (MHz)

S-Parameters

Frequency	S11 Mag	S11 Ang	S21 Mag	S21 Ang	S12 Mag	S12 Ang	S22 Mag	S22 Ang
5.0	0.200	-146.00	18.830	-173.00	0.030	9.00	0.240	189.00
50.0	0.210	-174.00	18.440	149.00	0.030	-2.00	0.200	173.00
100.0	0.240	-180.00	16.680	118.00	0.040	-6.00	0.220	161.00
150.0	0.270	172.00	14.750	91.00	0.040	-12.00	0.210	137.00

Absolute Maximum Conditions

Maximum Operating Temperature	-55.0 - 100.0 °C	Maximum Storage Temperature	-62.0 - 125.0 °C
Maximum Case Temperature	125.0 °C	Maximum Supply Voltage	10.0 Volts
Continuous RF Input Power	13.0 dBm	Short Term RF Input Power (1 minute max)	50.0 mW
Maximum Peak Power (3 µsec max)	0.5 W		

Amplifonix | 2707 Black Lake Place | Philadelphia, PA 19154
Tel: 215.464.4000 | FAX: 215.464.4001 | Email: info@amplifonix.com

i2 Technologies US, Inc.

HTML Pages converted to PDF Document

This document contain component information from the manufacturer's website which are not available in a revision controlled document from the manufacturer. To facilitate the addition of these parts into the Electronics Database, we are converting the HTML pages related to that part, from the manufacturer's website into Adobe PDF format. The contents of this document is based on the information provided on the manufacturer's website, therefore the information may have been changed by the manufacturer since this was created.

