


## Avalanche Surface Mount Rectifiers


**DO-214AA (SMB)**

| PRIMARY CHARACTERISTICS                  |        |
|--|--------|
| $I_{F(AV)}$                              | 3.0 A  |
| $V_{RRM}$                                | 600 V  |
| $I_{FSM}$                                | 90 A   |
| $E_{AS}$                                 | 20 mJ  |
| $V_F$ at $I_F = 3.0$ A ( $T_A = 125$ °C) | 0.86 V |
| $T_J$ max.                               | 175 °C |

### TYPICAL APPLICATIONS

For use in general purpose rectification of power supplies, inverters, converters, and freewheeling diodes for consumer, automotive, and telecommunication.

### FEATURES

- Low profile package
- Ideal for automated placement
- Glass passivated chip junction
- Controlled avalanche characteristics
- Low leakage current
- High forward surge capability
- AEC-Q101 qualified
- Meets MSL level 1, per J-STD-020, LF maximum peak of 260 °C
- Compliant to RoHS Directive 2002/95/EC and in accordance to WEEE 2002/96/EC
- **Halogen-free according to IEC 61249-2-21 definition**



**RoHS**  
COMPLIANT  
HALOGEN  
**FREE**

### MECHANICAL DATA

**Case:** DO-214AA (SMB)

Molding compound meets UL 94 V-0 flammability rating

Base P/N-M3 - halogen-free, RoHS compliant, and commercial grade

Base P/NHM3 - halogen-free, RoHS compliant, and AEC-Q101 qualified

**Terminals:** Matte tin plated leads, solderable per J-STD-002 and JESD 22-B102

M3 suffix meets JESD 201 class 1A whisker test, HM3 suffix meets JESD 201 class 2 whisker test

**Polarity:** Color band denotes cathode end

| MAXIMUM RATINGS ( $T_A = 25$ °C unless otherwise noted)                               |                |                       |      |
|---|----------------|-----------------------|------|
| PARAMETER   | SYMBOL         | AS3BJ                 | UNIT |
| Device marking code   |                | A3J                   |      |
| Maximum repetitive peak reverse voltage   | $V_{RRM}$      | 600                   | V    |
| Maximum DC forward current (fig. 1)   | $I_F$ (1)      | 3.0                   | A    |
|   | $I_F$ (2)      | 2.0                   |      |
| Peak forward surge current 10 ms single half sine-wave, non-repetitive, $T_J = 25$ °C | $I_{FSM}$      | 90                    | A    |
| Non-repetitive avalanche energy at $T_J = 25$ °C                                      | $E_{AS}$       | $I_{AS} = 2.0$ A max. | 20   |
|   |                | $I_{AS} = 1.0$ A typ. | 30   |
| Operating junction and storage temperature range                                      | $T_J, T_{STG}$ | - 55 to + 175         | °C   |

### Notes

(1) Mounted on 14 mm x 14 mm x 2 areas, 1 oz. FR4 PCB

(2) Free air, mounted on recommended 1.52 mm x 2.18 mm x 2 pad areas

| ELECTRICAL CHARACTERISTICS ( $T_A = 25\text{ }^\circ\text{C}$ unless otherwise noted) |   |                                   |             |      |               |               |
|---|---|-----------------------------------|-------------|------|---------------|---------------|
| PARAMETER   | TEST CONDITIONS   | SYMBOL                            | TYP.        | MAX. | UNIT          |               |
| Instantaneous forward voltage   | $I_F = 1.5\text{ A}$  | $T_A = 25\text{ }^\circ\text{C}$  | $V_F^{(1)}$ | 0.90 | -             | V             |
|   | $I_F = 3.0\text{ A}$  |                                   |             | 0.98 | 1.05          |               |
|   | $I_F = 1.5\text{ A}$  | $T_A = 125\text{ }^\circ\text{C}$ |             | 0.78 | -             |               |
|   | $I_F = 3.0\text{ A}$  |                                   |             | 0.86 | 0.95          |               |
| Reverse current   | $V_R = 600\text{ V}$  | $T_A = 25\text{ }^\circ\text{C}$  | $I_R^{(2)}$ | 0.5  | 20            | $\mu\text{A}$ |
|   |   | $T_A = 125\text{ }^\circ\text{C}$ |             | 40   | 150           |               |
| Typical reverse recovery time   | $I_F = 0.5\text{ A}$ , $I_R = 1.0\text{ A}$ ,<br>$t_{rr} = 0.25\text{ A}$ | $t_{rr}$                          | 1.5         | -    | $\mu\text{s}$ |               |
| Typical junction capacitance per diode  | Rated $V_R = 4.0\text{ V}$ , 1 MHz  | $C_J$                             | 40          | -    | pF            |               |

**Notes**

- (1) Pulse test: 300  $\mu\text{s}$  pulse width, 1 % duty cycle
- (2) Pulse test: Pulse width  $\leq 40\text{ ms}$

| THERMAL CHARACTERISTICS ( $T_A = 25\text{ }^\circ\text{C}$ unless otherwise noted) |                       |       |                    |
|--|-----------------------|-------|--------------------|
| PARAMETER  | SYMBOL                | AS3BJ | UNIT               |
| Typical thermal resistance   | $R_{\theta JA}^{(1)}$ | 100   | $^\circ\text{C/W}$ |
|  | $R_{\theta JM}^{(2)}$ | 14    |                    |

**Notes**

- (1) Free air, mounted on recommended PCB 1 oz. pad area; thermal resistance  $R_{\theta JA}$  - junction to ambient
- (2) Units mounted on PCB with 14 mm x 14 mm x 2 areas, 1 oz. copper pad areas;  $R_{\theta JM}$  - junction to mount

| ORDERING INFORMATION (Example) |                 |                        |               |                                    |
|--------------------------------|-----------------|------------------------|---------------|------------------------------------|
| PREFERRED P/N                  | UNIT WEIGHT (g) | PREFERRED PACKAGE CODE | BASE QUANTITY | DELIVERY MODE                      |
| AS3BJ-M3/52T                   | 0.096           | 52T                    | 750           | 7" diameter plastic tape and reel  |
| AS3BJ-M3/5BT                   | 0.096           | 5BT                    | 3200          | 13" diameter plastic tape and reel |
| AS3BJHM3/52T (1)               | 0.096           | 52T                    | 750           | 7" diameter plastic tape and reel  |
| AS3BJHM3/5BT (1)               | 0.096           | 5BT                    | 3200          | 13" diameter plastic tape and reel |

**Note**

- (1) AEC-Q101 qualified

## RATINGS AND CHARACTERISTICS CURVES

( $T_A = 25\text{ }^\circ\text{C}$  unless otherwise noted)




Fig. 1 - Maximum Forward Current Derating Curve




Fig. 2 - Forward Power Loss Characteristics




Fig. 3 - Typical Instantaneous Forward Characteristics




Fig. 5 - Typical Junction Capacitance




Fig. 4 - Typical Reverse Characteristics





Fig. 6 - Typical Transient Thermal Impedance

**PACKAGE OUTLINE DIMENSIONS** in inches (millimeters)




## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk and agree to fully indemnify and hold Vishay and its distributors harmless from and against any and all claims, liabilities, expenses and damages arising or resulting in connection with such use or sale, including attorneys fees, even if such claim alleges that Vishay or its distributor was negligent regarding the design or manufacture of the part. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.