




Home > Products > MICRO SWITCH™ Sealed and High Accuracy Switches > AT > Product Page

Order Product and Get Support

- U.S. Authorized Distributors
- Global Sales & Service
- N. American Sales Reps
- Distributor Inventory
- Technical Assistance
- White Papers
- Literature Request
- Test and Measurement Catalog
- RoHS Product List
- Customer Feedback

64AT34-3D



Actual product appearance may vary.

AT Series Toggle Switch, 4 pole, 2 position, H58 terminal, Locking Lever

Features

Gold or silver contacts
 Choice of sealed bushing
 Standard or pull to unlock toggle lever
 Short behind-panel depth
 Solder or quick connect termination
 2, 4, 6, or 8 SPDT precision basic switches
 2 or 3 position, momentary or maintained action

Potential Applications

Industrial machinery and equipment
 Military and commercial aviation
 Construction equipment
 Test instruments
 Agricultural machinery
 Process control
 Medical instrumentation

Description

Compact multipole 2, 4, 6, or 8 SPDT design. MICRO SWITCH™ precision basic switches conserve space and weight. Pull-to-Unlock Toggle Levers prevent accidental operation: the lever must be pulled approximately 2,3 mm [0.09 inches] to change the positions. Many locking configurations are available. Lever to bushing seals. Hermetic basic switches are available. AT qualified versions meet MIL-8805/98. Various levers and styles are available.

Supporting Documentation

[Accessory: Seals](#)

[Accessory: Nuts](#)

[Engineering Drawing](#)

Product Specifications																																		
Circuitry/Operating action	<table border="0" style="width: 100%; text-align: center;"> <tr> <td></td> <td>Keyway</td> <td>Opposite Keyway</td> </tr> <tr> <td></td> <td>Maintained</td> <td>Maintained</td> </tr> <tr> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>NC COM NO</td> <td>NC COM NO</td> </tr> <tr> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>NC COM NO</td> <td>NC COM NO</td> </tr> <tr> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>NC COM NO</td> <td>NC COM NO</td> </tr> <tr> <td></td> <td></td> <td></td> </tr> <tr> <td></td> <td>NC COM NO</td> <td>NC COM NO</td> </tr> <tr> <td></td> <td>ON</td> <td>OFF</td> </tr> </table>		Keyway	Opposite Keyway		Maintained	Maintained					NC COM NO	NC COM NO					NC COM NO	NC COM NO					NC COM NO	NC COM NO					NC COM NO	NC COM NO		ON	OFF
	Keyway	Opposite Keyway																																
	Maintained	Maintained																																
	NC COM NO	NC COM NO																																
	NC COM NO	NC COM NO																																
	NC COM NO	NC COM NO																																
	NC COM NO	NC COM NO																																
	ON	OFF																																
Product Type	MICRO SWITCH™ Toggle																																	
Ampere/Voltage Range (Resistive Load)	0.1 A to 1.0 A at 0.5 Vac to 115 Vac, 0.1 A to 1.0 A at 0.5 Vdc to 28 Vdc																																	
Circuitry	4PDT																																	
Action	2 position																																	
Mounting	Bushing 15/32 in																																	
Termination	H58																																	
Comment	FAA-PMA approved, contains 24K solid gold contacts																																	
Availability	Global																																	
UNSPSC Code	30211908																																	
UNSPSC Commodity	30211908 Toggle switches																																	
Series Name	AT																																	

My Links

[Login to iCOM](#)
[Login as Rep/AD](#)
[Login as Guest](#)
[Login to Digital University](#)

Keyword Search

Search for product and support information.

All Sensing and Control

Product Search

Part number search:

Use (*) to expand search

[Specification Search](#)