




SOD-323


Features

- ◊ Small surface mounting type.
- ◊ High Speed.($t_{rr}=1.2\text{ns}$ Typ.)
- ◊ High reliability with high surge current handling capability.

Maximum Ratings and Electrical Characteristics

Rating at 25°C ambient temperature unless otherwise specified.

Dimensions in inches and (millimeters)

Maximum Ratings

Parameter	Symbol	Limits		Unit
Non-Repetitive Peak reverse voltage	V_{RM}	90		V
DC Blocking Voltage	V_R	80		V
Peak forward Current	I_{FM}	225		mA
Average Rectified Output Current	I_O	100		mA
Surge current (1s)	I_{surge}	500		mA
Junction temperature	T_j	125		°C
Storage temperature	T_{STG}	-55~+125		°C

Electrical Ratings

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions
Forward voltage	V_F			1.2	V	$I_F=100\text{mA}$
Reverse current	I_R			0.1	μA	$V_R=80\text{V}$
Capacitance between terminals	C_T			3	pF	$V_R=0.5\text{V}, f=1\text{MHz}$
Reverse Recovery Time	t_{rr}			4	ns	$I_F=10\text{mA}, V_R=6\text{V}, R_L=100\Omega$

Typical Characteristics

● Electrical characteristic curves ($T_a=25^\circ\text{C}$)




Fig.1 Forward characteristics




Fig.2 Reverse characteristics




Fig.3 Capacitance between terminals characteristics




Fig.4 Reverse recovery time characteristics




Fig.5 Surge current characteristics