

9V AC-DC Switching Power Supply



Specifications

AC Input

Voltage Range: 90 – 264 VAC
Input Frequency: 47 – 63 Hz
Inrush Current: 30A Max

DC Output

Voltage Range: 8.55V – 9.45V
Current Range: 0.1A – 1A



Reliability

Insulation Resistance: 50MΩ Min (Input to Output, DC 500V)
MTBF: 50000 Hours

Plug Types



Ordering Information

NTE Type No.	DC Output		Plug Type
	Amps	Wattage	
57-9D-500-1	500mA	4.5	2.1mm x 5.5mm Jack
57-9D-500-2	500mA	4.5	2.5mm x 5.5mm Jack
57-9D-500-3	500mA	4.5	1.35mm ID x 3.5mm OD Plug
<i>NEW</i> 57-9D-500-4	500mA	4.5	2.1mm ID x 5.5mm OD Plug
<i>NEW</i> 57-9D-500-5	500mA	4.5	2.5mm ID x 5.5mm OD Plug
57-9D-600-1	600mA	5.4	2.1mm x 5.5mm Jack
57-9D-600-2	600mA	5.4	2.5mm x 5.5mm Jack
<i>NEW</i> 57-9D-600-4	600mA	5.4	2.1mm ID x 5.5mm OD Plug
<i>NEW</i> 57-9D-600-5	600mA	5.4	2.5mm ID x 5.5mm OD Plug
57-9D-1000-1	1A	10	2.1mm x 5.5mm Jack
57-9D-1000-2	1A	10	2.5mm x 5.5mm Jack
57-9D-1000-3	1A	10	1.35mm ID x 3.5mm OD Plug
<i>NEW</i> 57-9D-1000-4	1A	10	2.1mm ID x 5.5mm OD Plug
<i>NEW</i> 57-9D-1000-5	1A	10	2.5mm ID x 5.5mm OD Plug