



- Wrapost double row strip sockets are available with one to four-level wrapposts: M-M# 0040, 0089, 0088, or 0086 pins. See page 162 for details.
- Hi-Rel, 4-finger #30 BeCu contact is rated at 3 amps. See page 208 for details.



Ordering Information

Fig. 1	Series 421...001 1 Level Wrappost
	421-XX-2_ _ -41-001000 Specify # of pins → 02-64
Fig. 2	Series 422...001 2 Level Wrappost
	422-XX-2_ _ -41-001000 Specify # of pins → 02-64
Fig. 3	Series 423...001 3 Level Wrappost
	423-XX-2_ _ -41-001000 Specify # of pins → 02-64
Fig. 4	Series 424...002 4 Level Wrappost
	424-XX-2_ _ -41-002000 Specify # of pins → 02-64

XX=Plating Code
See Below



For RoHS compliance, select \diamond plating code. For the all gold option (XX=13) also change part number from 42X-XX-2XX-41-00X000 to 42X-13-2XX-41-00X100

SPECIFY PLATING CODE XX=	13 \diamond	93	43 \diamond
Sleeve (Pin)	0,25µm Au	5,08µm Sn/Pb	5,08µm Sn
Contact (Clip)	0,76µm Au	0,76µm Au	0,76µm Au