High Performance BGA Cooling Solutions w/ Thermal Tape Attachment





ATS Part#: ATS-55425K-C1-R0

Description: High Performance X-CUT - Heat Sink, T412, BLACK-ANODIZED

Heat Sink Type: Cross-Cut

Heat Sink Attachment: THERMAL TAPE

Equivalent Part Number: ATS-55425K-C2-R0

*Image above is for illustration purpose only.

Features & Benefits

- · High efficiency cross-cut fin design provides low pressure drop characteristics
- · Large surface area increases heat sink performance
- Designed specifically for BGAs and other surface mount packages
- Comes pre-assembled with high performance thermal interface material

Thermal Performance

AIR VELOCITY		@200 LFM 1.0 M/S	@300 LFM 1.5 M/S	@400 LFM 2.0 M/S	@500 LFM 2.5 M/S	@600 LFM 3.0 M/S	@700 LFM 3.5 M/S	@800 LFM 4.0 M/S
THERMAL RESISTANCE	Unducted Flow	4.71 °C/W	3.70 °C/W	3.20 °C/W	2.88 °C/W	2.64 °C/W	2.45 °C/W	2.31 °C/W
	Ducted Flow	n/a						

Product Detail

Schematic Image	Dimension A	Dimension B	Dimension C	Dimension D	TIM	Finish
	42.5 mm	42.5 mm	14.5 mm	mm	T412	BLACK-ANODIZED
*Image above is for illustration purpose only.	Dimensio ATS-5542 (Saint Go Thermal papplicatio ATS rese performar ATS certifications.	25K-C2-R0 is the exbain C675). performance data arin. rives the right to uponce.	height from the botto act heat sink asserr e provided for refere ate or change its pro-	om of the base to the ably with an equivale ence only. Actual percoducts without notice S-6 and REACH conable.	nt therma	al interface material



