

General Description

The Ultraslow Capacitance Transient Voltage Suppressors are designed to low voltage, integrated circuits from transients caused by electrostatic discharge (ESD), electrical fast transients (EFT), Surge and other induced voltages.

Applications

- Ethernet – 10/100/1000 Base T
- Cellular Phones
- Handheld – Wireless Systems
- Personal Digital Assistant(PDA)
- USB Interface

IEC61000-4-2(ESD) 15kV(air), 8kV(Contact)


IEC61000-4-4(EFT) 40A(5/50ns)

IEC61000-4-5(Surge)24A(8/20us),Level2(Line-G round)& Level 2(Line- Line)


Features

- 350 W Peak Pulse Power per Line (tp=8/20μs)
- Unidirectional & Bidirectional Configurations
- Replacement for MLV (0805)
- Protects One Power or I/O Port
- ESD Protection > 40 kilovolts
- Low Clamping Voltage
- Available in Multiple Voltage Type Ranging from 3V to 8 V
- Ultra Low Capacitance:3pF Typical
- **Pb-Free package is available**
RoHS product for packing code suffix "G"
Halogen free product for packing code suffix "H"
- Moisture Sensitivity Level 1


SOD-323



UNIDIRECTIONAL



BIDIRECTIONAL



Absolute Maximum Ratings @ 25°C Unless Otherwise Specified

Parameter	Symbol	Value	Units
Peak Pulse Power (tp = 8/20μs) - See Fig1.	P _{PP}	350	W
Storage Temperature Range	T _{STG}	-55 to 150	°C
Operating Junction Temperature Range	T _J	-55 to 150	°C

Electrical Characteristics Per line @ 25°C Unless Otherwise Specified

Part Numbers	V _{BR}			I _T	V _{RM}	I _{RM}	V _F	I _F	C
	Min.	Typ.	Max.				Max.		Typ. 0v bias
	V	V	V				V		pF
SEBLC03	3.3	3.8	4.5	1	3	1	1.25	200	3
SEBLC03C	3.3	3.8	4.5	1	3	1	1.25	200	3
SEBLC05	6.1	6.7	7.2	1	5	1	1.25	200	3
SEBLC05C	6.1	6.7	7.2	1	5	1	1.25	200	3
SEBLC08C	8.6	9.5	10.2	1	8	1	1.25	200	3
SEBLC12C	13.5	14.6	15.7	1	12	1	1.25	200	3




Fig1. Peak Pulse Power VS Pulse Time





Fig2. Pause Wave Form

SOD-323 Mechanical Data



Dimensions in inches and (millimeters)

Marking

Type number	Marking code
SEBLC03 / SEBLC03C	03 / 03C
SEBLC05 / SEBLC05C	05 / 05C
SEBLC08C	08C
SEBLC12C	2C

Ordering Information:

Device PN	Packing
Part Number -T ⁽¹⁾ G ⁽²⁾ -WS	Tape&Reel: 3 Kpcs/Reel

Note: (1) Packing code, Tape & Reel Packing

(2) RoHS product for packing code suffix "G" ; Halogen free product for packing code suffix "H"

*****Disclaimer*****

WILLAS reserves the right to make changes without notice to any product specification herein, to make corrections, modifications, enhancements or other changes. WILLAS or anyone on its behalf assumes no responsibility or liability for any errors or inaccuracies. Data sheet specifications and its information contained are intended to provide a product description only. "Typical" parameters which may be included on WILLAS data sheets and/ or specifications can and do vary in different applications and actual performance may vary over time. WILLAS does not assume any liability arising out of the application or use of any product or circuit.

WILLAS products are not designed, intended or authorized for use in medical, life-saving implant or other applications intended for life-sustaining or other related applications where a failure or malfunction of component or circuitry may directly or indirectly cause injury or threaten a life without expressed written approval of WILLAS. Customers using or selling WILLAS components for use in such applications do so at their own risk and shall agree to fully indemnify WILLAS Inc and its subsidiaries harmless against all claims, damages and expenditures.