


- Fully Insulated
- Metal Insulation Sleeve
- Molded Insulator
- Internal Barrel Serrations
- Funnel Entry



Nylon Fully Insulated Bullet Receptacles

Catalog Number	Wire Range	Dimension <small>inch mm</small>					
		W	F	L	B	D	T
KNF18-4FB-M	22-16 A.W.G. 0.5-1.5 mm ²	.153 3.9	.287 7.3	.992 25.2	.433 11.0	.157 4.0	.016 0.4
KNF14-4FB-M	16-14 A.W.G. 1.5-2.5 mm ²	.153 3.9	.287 7.3	.992 25.2	.433 11.0	.197 5.0	.016 0.4

Box Quantity: (M)=1000
For Mylar Tape replace box quantity with (T). Example: KNF18-4FB-T
UL File #E66716
CSA File #LR4503

See pages in back of catalog for complete tool information.
Tool and Die Selection Chart on page M42.

Maximum Electrical Rating: 105°C 600 Volts Max.
Terminal Material: Brass with Copper Sleeve



Vinyl Fully Insulated Bullet Receptacles

Catalog Number	Wire Range	Dimension <small>inch mm</small>					
		W	F	L	B	D	T
KVF18-4FB-M	22-16 A.W.G. 0.5-1.5 mm ²	.153 3.9	.287 7.3	.917 23.3	.413 10.5	.150 3.8	.016 0.4
KVF14-4FB-M	16-14 A.W.G. 1.5-2.5 mm ²	.153 3.9	.287 7.3	.917 23.3	.413 10.5	.185 4.7	.016 0.4
KVF10-5FB-D*	12-10 A.W.G. 4-6 mm ²	.193 4.9	.276 7.0	.988 25.1	.492 12.5	.244 6.2	.018 0.45

*Not UL listed
Box Quantity: (D)=500; (M)=1000
For Mylar Tape replace box quantity with (T). Example: KVF18-4FB-T
UL File #E66716
CSA File #LR4503

See pages in back of catalog for complete tool information.
Tool and Die Selection Chart on page M42.

Maximum Electrical Rating: 75°C 300 Volts Max.
Terminal Material: Brass with Copper Sleeve

Tools used with Nylon and Vinyl Insulated Bullet Receptacles



ERG2500



KT-2500