

Type No.	Pin Configuration	Features	CTR (%)			I _F (mA)	V _{CE0} (V)	BV _s (V _{rms})	Safety Standard (Note 2)										
			Rank	Min.	Max.				UL	TÜV	VDE	BSI							
TLP504A		Standard	—	50	600	5	55	2,500	○										
TLP504A-2		Two channels of TLP504A	—	50					600	△									
TLP521-1		4 pin small package Standard	A	50	600	5	55	2,500		○									
			GB	100															
			BL	200															
			YG	50	300														
			GR	100															
			GRL	100	200														
			GRH	150	300														
Y	50	150																	
TLP521-2		Two channels of TLP521-1	A	50	600														
			GB	100															
			BL	200	300														
			GR	100															
TLP521-3		Three channels of TLP521-1	A	50	600														
			GB	100															
TLP521-4		Four channels of TLP521-1	A	50	600														
			GB	100															
TLP531		Standard	A	50	600	±5	55	5,000	○	△ VDE 0884	○ VDE 0884 Option (D4)	○ 415							
			GB	100															
			BL	200	300														
			YG	50															
			GR	100															
TLP532		Standard No internal base connection	Y	50	150														
			A	50	600														
			GB	100															
			BL	200	300														
			YG	50															
TLP620		AC input 4 pin small package VDE0884 approved with option (D4)	—	50	600														
			GB	100															
			GR	100									300						
TLP620-2		Two channels of TLP620	—	50	600														
			GB	100															