



POR-1222 □□□□ □□: 1

2-Port Outdoor Gigabit PoE-Plus Repeater

Extend the reach of your Gigabit PoE-Plus devices

For system integrators looking for a professional solution to help extend their Outdoor Gigabit PoE (802.3af/at) network, POR-1222 is the perfect accessory to increase your network performance. As a 2-port repeater, it's now easier to add more devices to the network for greater deployment flexibility.

Normal cable runs only reach 100 meters, but with POR-1222 installers can extend the PoE network performance up to 200 meters. Furthermore, you can triple your range or even more by daisy-chaining* multiple PoE repeaters.

* Maximum distance depends on the required Wattage of the PD.

Simple yet durable, no software required


As a Gigabit PoE-Plus Repeater, POR-1222 receives all power from the Power Sending Equipment (PSE), such as a Gigabit PoE-Plus switch. This means that POR-1222 uses no external power supply, making it the most flexible option for system integrators looking for an easy, affordable solution to increase the distance to the attached devices on a network. POR-1222 has 3 RJ-45 ports for easy deployment, 1 "IN" port that accepts the power and data for the first 100 meters, and 2 "OUT" ports that boosts and extends the power and data an additional 100 meters. With a durable metal housing, POR-1222 fits into any tight deployments.

Applications

POR-1222 is a long-ranged solution for deploying PoE IP Digital Signage and any Gigabit PoE PD powered by 802.3at Gigabit PSE.

IP65-compliant

The POR-1222 is compliant to IP65, and is therefore weatherproof from snow, rain, storms, desert heat, etc. For deployment in any harsh weather conditions, this PoE Repeater is up to the challenge.



1. PoE In
2. PoE Out

Key Features

- PoE 10/100/1000Mbps 2 PoE ports
- 10/100/1000Mbps RJ-45 ports
- Weatherproof IP65-rated housing
- IEEE 802.3af / at PoE compliant
- (802.3af/at PoE) IEEE 802.3af/at PoE
- 100m PoE range
- Multiple PoE repeaters can be deployed by daisy chain to extend range
- PoE repeaters can be deployed by daisy chain to extend range

System Specifications

Connectors and Cabling:

- 1 x 10/100/1000Base-T RJ-45 PoE Input Port
- 2 x 10/100/1000Base-T RJ-45 PoE Output Port

Power:

- PoE Power Input: 44-57 Volt
- Power Consumption: 2.5W (Max.)

Standards & Protocols:

- IEEE 802.3 10Base-T, Ethernet
- IEEE 802.3u 100Base-TX, Fast Ethernet
- IEEE802.3ab 1000Base-T, Gigabit Ethernet
- IEEE 802.3x Ethernet Flow Control
- IEEE 802.3af Power over Ethernet (PoE)
- IEEE 802.3at Power over Ethernet Plus (PoE+)

Physical Specifications

Dimensions (W x D x H mm):

195 x 160 x 95mm

Weight (g):

700 g

Enclosure:

Weatherproof IP65-rated housing

Features

PoE:

IEEE 802.3af/at compliant

Environment

Temperature (°C):

Operating: 0°C ~ 50°C

Storage: 0°C ~ 70°C

Humidity (Non-condensing):

Storage: 5% to 95%

Operating: 5 ~ 95%


Others

Approval and Compliance:

FCC Part 15, CE

Deployment:

Wall/Pole mount



Order Information

POR-1222

Package Contents

Mounting Kit

Quick Installation Guide

No responsibility for any errors or omissions. All mentioned brand names are registered trademarks and property of their owners.
Copyright © Digital Data Communications GmbH, Germany. All Rights Reserved.