



NOTES.

1. FOR USE WITH BELDEN 5422 CABLE.
2. SAME AS 1965-3 EXCEPT FOR FINISH.
3. FOR CABLING INSTRUCTIONS SEE C-59-315-1.

UNLESS OTHERWISE SPECIFIED:

- | | |
|--|---|
| <ol style="list-style-type: none"> 1. TOLERANCES: FRACTIONS ± .010 DECIMALS ± .004 ANGLES ± 0° 30' T. I. R. CONCENTRICITY OF ANY 2 DIAMETERS MAY NOT EXCEED THE SUM OF THEIR TOLERANCES. | <ol style="list-style-type: none"> 2. REMOVE ALL BURRS. BREAK SHARP EDGES .003 MAX. 3. NO FILLETS PERMITTED. 4. SURFACE ROUGHNESS 63 MICROINCHES RMS MAX. 5. ALL DIMENSIONS PRIOR TO PLATING. |
|--|---|

| | | | |
|-----------|---|----------------|----------------|
| 17 | 1 | INSULATOR | C-59-187-4-M99 |
| 16 | 1 | BAYONET SLEEVE | |
| 15 | 1 | INSULATOR | C-59-187-3-M99 |
| 14 | 1 | OUTER CONTACT | C-59-187-2-M99 |
| 13 | 1 | BNC CONTACT M | 1-4896-3MA9 |
| 12 | 1 | GASKET | |
| 11 | 1 | SPRING WASHER | |
| 10 | 1 | CAM LEVER | |
| 7 | 1 | INSULATOR | C-59-187-5-M99 |
| 6 | 1 | RETAINER | 1-1119-1M06 |
| 5 | 1 | BRAID CLAMP | 631-5-M06 |
| 4 | 1 | GASKET | 631-6-M99 |
| 3 | 1 | WASHER | 260C-1-M06 |
| 2 | 1 | BODY | C-59-166-6-M06 |
| 1 | 1 | CLAMP NUT | 631-4-M06 |
| ITEM REQD | | DESCRIPTION | DWG NO |

REVISIONS

| ISSUE | CHANGES |
|-------|----------------------------|
| 0 | ER 10818 NLA 24 FEB 72 |
| 1 | CN 15918A GA 15 JUL 76 |
| 2 | CN 25083 C SL 1 SEP 83 |
| 3 | CN 34639 C KH 17 MAY 93 |
| 4 | CN 35740 A KH 12 AUG 94 |

1965-3-9S.D

S-D

**BNC TRIAX
PLUG**

DRAWN NLA DATE 23 FEB 72

APPR. J.M. DATE 24 FEB 72

KINGS ELECTRONICS
40 HANBLEDALE ROAD
TUCKAHOE, N. Y.

1965-3-9S.D