# BGA Heat Sink (High Aspect Ratio Ext.) Slant Fin





ATS Part#:

Description:

#### ATS017017005-MF-5D

on: 17.00 :

17.00 x 17.00 x 5.00 mm BGA Heat Sink (High Aspect Ratio Ext.) Slant Fin

| Heat Sink Type:         | Slant Fin |
|-------------------------|-----------|
| Heat Sink Attachment:   | N/A       |
| Equivalent Part Number: | N/A       |

\*Image above is for illustration purpose only.

### **Features & Benefits**

- Features a low profile, slant fin array that offers many of the performance benefits of maxiFLOW™ at a great value
- Fabricated from extruded aluminum, which minimizes thermal resistance from the base to the fins, reduces weight and keeps costs low
- Higher performance helps ensure reliable product life at a lower cost than other extruded heat sinks
- · Comes standard without interface material or with most common pressure sensitive thermal tapes as a custom option

## **Thermal Performance**

| AIR VELOCITY       |               | @200 LFM<br>1.0 M/S | @300 LFM<br>1.5 M/S | @400 LFM<br>2.0 M/S | @500 LFM<br>2.5 M/S | @600 LFM<br>3.0 M/S | @700 LFM<br>3.5 M/S | @800 LFM<br>4.0 M/S |
|--------------------|---------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|
| THERMAL RESISTANCE | Unducted Flow | 33.64 °C/W          | 26.5 °C/W           | 22.8 °C/W           | 20.4 °C/W           | 18.7 °C/W           | 17.4 °C/W           | 16.3 °C/W           |
|                    | Ducted Flow   | 17.9                | 15                  | 13.3                | 12.1                | 11.2                | 10.4                | 9.8                 |

## **Product Detail**

| Schematic Image                                | Dimension A  | Dimension B | Dimension C | Dimension D | тім | Finish         |  |
|--|--|-------------|-------------|-------------|-----|----------------|--|
|  | 17.00 mm   | 17.00 mm    | 5.00 mm     | 18.06 mm    | N/A | BLACK-ANODIZED |  |
|  | <ul> <li>Notes:</li> <li>Dimension A and B refer to component size.</li> <li>Dimension C is the heat sink height from the bottom of the base to the top of the fin field.</li> <li>Dimension D is fin tip to fin tip.</li> <li>Thermal performance data are provided for reference only. Actual performance may vary by application.</li> <li>ATS reserves the right to update or change its products without notice to improve the design or performance.</li> <li>ATS certifies that this heat sink assembly is RoHS-6 and REACH compliant.</li> <li>Contact ATS to learn about custom options available.</li> </ul> |             |             |             |     |                |  |
| *Image above is for illustration purpose only. |  |             |             |             |     |                |  |

For more information, to find a distributor or to place an order, please contact us at 781-769-2800 (North America), sales@qats.com or www.qats.com.



© 2013 Advanced Thermal Solutions, Inc. | 89-27 Access Road | Norwood MA | 02062 | USA