

Selection Charts



240 X 480 PRIMARY VOLTS — 120/240 SECONDARY VOLTS — FOUR WINDING — 1Ø, 60 Hz

KVA	GROUP I CATALOG NO. 80°C RISE	GROUP II CATALOG NO. 115°C RISE	APPROX. DIMENSIONS Inches (Cm.)			APPROX. SHIP WEIGHT Lbs. (Kg.)	TYPE MTG. W – Wall F – Floor	WEATHER SHIELD P/N	Electrical Connections and Design Figures Begin on Page 42
			HEIGHT	WIDTH	DEPTH				
37.5	T-2-53019-8S	T-2-53019-1S	25.50 (64.8)	24.39 (61.9)	19.37 (49.2)	350 (159.0)	F ①	WS-A-1	5-E
50.0	T-2-53020-8S	T-2-53020-1S	35.90 (91.2)	31.90 (81.0)	26.88 (68.3)	425 (193.0)	F	WS-A-3	5-E
75.0	T-2A-53021-8S	T-2A-53021-1S	35.90 (91.2)	31.90 (81.0)	26.88 (68.3)	525 (238.0)	F	WS-A-3	5-E
100.0	T-1-53022-8S	T-1-53022-1S	42.00 (106.7)	40.00 (101.6)	30.00 (76.2)	725 (329.0)	F	WS-A-53	5-E
167.0	T-1-53023-8S	T-1-53023-1S	60.00 (152.4)	41.00 (104.1)	36.00 (91.4)	1675 (760.0)	F	WS-B-1	5-E

NEW

600 PRIMARY VOLTS — 120/240 SECONDARY VOLTS — 1Ø, 60 Hz

KVA	GROUP III CATALOG NO. 80°C RISE	GROUP IV CATALOG NO. 115°C RISE	APPROX. DIMENSIONS Inches (Cm.)			APPROX. SHIP WEIGHT Lbs. (Kg.)	TYPE MTG. W – Wall F – Floor	WEATHER SHIELD P/N	Electrical Connections and Design Figures Begin on Page 42
			HEIGHT	WIDTH	DEPTH				
37.5	T-2-53119-8S	T-2-53119-1S	29.90 (75.9)	28.20 (71.6)	22.40 (56.9)	340 (154.0)	F ①	WS-A-2	11-E
50.0	T-2-53120-8S	T-2-53120-1S	35.90 (91.2)	31.90 (81.0)	26.88 (68.3)	420 (191.0)	F	WS-A-3	11-E
75.0	T-2-53121-8S	T-2-53121-1S	35.90 (91.2)	31.90 (81.0)	26.88 (68.3)	525 (238.0)	F	WS-A-3	11-E
100.0	T-1-53122-8S	T-1-53122-1S	42.00 (106.7)	40.00 (101.6)	30.00 (76.2)	700 (318.0)	F	WS-A-53	11-E

① Wall mounting brackets are available for these sizes, refer to page 50.