


30V Dual N- and P-channel Trench MOSFET

Features

- Low $V_{GS(th)}$: $V_{GS(th)}=1.0\sim 3.0V$
- Small footprint due to small package
- Low $R_{GDS(on)}$: N-ch, $R_{DS(on)}=24m\Omega$ (@ $V_{GS}=10V, I_D=2.9A$)
P-ch, $R_{DS(on)}=66m\Omega$ (@ $V_{GS}=-10V, I_D=-2.7A$)


Ordering Information

Part Number	Marking Code	Package
SUF2001	SUF2001	SOP-8



SOP-8

Marking Information



Column 1: Device Code
 Column 2: Production Information
 - . Y: Year Code
 - . WW: Week Code

Absolute maximum ratings ($T_A=25^\circ C$ unless otherwise noted)

Characteristic	Symbol	Rating		Unit
		N-Ch	P-Ch	
Drain-source voltage	V_{DSS}	30	-30	V
Gate-source voltage	V_{GSS}	± 20		V
Drain current (DC)	I_D	5.8	-5.3	A
Drain current (Pulsed) *	I_{DP}	23.2	-21.2	A
Total power dissipation **	P_D	2		W
Avalanche current (Single)	I_{AS}	5.8 ^②	-5.3 ^⑥	A
Single pulsed avalanche energy	E_{AS}	72 ^②	33 ^⑥	mJ
Avalanche current (Repetitive) ^①	I_{AR}	5.8	-5.3	A
Repetitive avalanche energy ^①	E_{AR}	3.4	1.6	mJ
Junction temperature	T_J	150		°C
Storage temperature range	T_{stg}	-55~150		
Thermal resistance junction to ambient	$R_{th(J-A)}$	62.5		°C/W

* Limited by maximum junction temperature

** Device mounted on a glass-epoxy board

N-channel MOSFET Electrical Characteristics

Characteristic	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Drain-source breakdown voltage	BV_{DSS}	$I_D=250\mu A, V_{GS}=0$	30	-	-	V
Gate threshold voltage	$V_{GS(th)}$	$I_D=250\mu A, V_{DS}=V_{GS}$	1.0	-	3.0	V
Drain-source cut-off current	I_{DSS}	$V_{DS}=30V, V_{GS}=0V$	-	-	1	μA
Gate leakage current	I_{GSS}	$V_{DS}=0V, V_{GS}=\pm 20V$	-	-	± 100	nA
Drain-source on-resistance	$R_{DS(on)}$	$V_{GS}=10V, I_D=2.9A$	-	24	30	$m\Omega$
		$V_{GS}=5.0V, I_D=2.9A$	-	28	34	$m\Omega$
Forward transfer conductance ^④	g_{fs}	$V_{DS}=5V, I_D=5.8A$	-	12	-	S
Input capacitance	C_{iss}	$V_{GS}=0V, V_{DS}=10V, f=1MHz$	-	370	560	pF
Output capacitance	C_{oss}		-	60	90	
Reverse transfer capacitance	C_{rss}		-	36	54	
Turn-on delay time ^{③④}	$t_{d(on)}$	$V_{DS}=15V, I_D=5.8A, R_G=10\Omega$	-	1.2	-	ns
Rise time ^{③④}	t_r		-	1.1	-	
Turn-off delay time ^{③④}	$t_{d(off)}$		-	2.5	-	
Fall time ^{③④}	t_f		-	1.1	-	
Total gate charge ^{③④}	Q_g	$V_{DS}=15V, V_{GS}=5V, I_D=5.8A$	-	4.2	6.3	nC
Gate-source charge ^{③④}	Q_{gs}		-	0.9	1.4	
Gate-drain charge ^{③④}	Q_{gd}		-	1.4	2.1	

Source-Drain Diode Ratings and Characteristics

Characteristic	Symbol	Test Condition	Min	Typ	Max	Unit
Source current	I_S	Integral reverse diode in the MOSFET	-	-	1.5	A
Source current(Pulsed) ^①	I_{SM}		-	-	6.0	
Forward voltage ^④	V_{SD}	$V_{GS}=0V, I_S=1.5A$	-	-	1.2	V
Reverse recovery time	t_{rr}	$I_S=1.5A, di_S/dt=100A/us$	-	90	-	ns
Reverse recovery charge	Q_{rr}		-	0.5	-	μC

Note ;

- ① Repetitive Rating : Pulse width limited by maximum junction temperature
- ② $L=3.4mH, I_{AS}=5.8A, V_{DD}=15V, R_G=25\Omega$
- ③ Pulse Test : Pulse Width < 300us, Duty cycle \leq 2%
- ④ Essentially independent of operating temperature

P-channel MOSFET Electrical Characteristics

Characteristic	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Drain-source breakdown voltage	BV_{DSS}	$I_D=250\mu A, V_{GS}=0$	-30	-	-	V
Gate threshold voltage	$V_{GS(th)}$	$I_D=250\mu A, V_{DS}=V_{GS}$	-1.0	-	-3.0	V
Drain-source cut-off current	I_{DSS}	$V_{DS}=-30V, V_{GS}=0V$	-	-	1	μA
Gate leakage current	I_{GSS}	$V_{DS}=0V, V_{GS}=\pm 20V$	-	-	± 100	nA
Drain-source on-resistance	$R_{DS(on)}$	$V_{GS}=-10V, I_D=-2.7A$	-	66	72	m Ω
		$V_{GS}=-5.0V, I_D=-2.7A$	-	77	83	m Ω
Forward transfer conductance ^⑧	g_{fs}	$V_{DS}=-5V, I_D=-5.3A$	-	11	-	S
Input capacitance	C_{iss}	$V_{GS}=0V, V_{DD}=-10V, f=1MHz$	-	390	590	pF
Output capacitance	C_{oss}		-	97	150	
Reverse transfer capacitance	C_{rss}		-	37	60	
Turn-on delay time ^{⑦⑧}	$t_{d(on)}$	$V_{DS}=-15V, I_D=-5.3A, R_G=10\Omega$	-	1.2	-	ns
Rise time ^{⑦⑧}	t_r		-	1.1	-	
Turn-off delay time ^{⑦⑧}	$t_{d(off)}$		-	2.5	-	
Fall time ^{⑦⑧}	t_f		-	1.1	-	
Total gate charge ^{⑦⑧}	Q_g	$V_{DS}=-15V, V_{GS}=-5V, I_D=-5.3A$	-	4.7	7.0	nC
Gate-source charge ^{⑦⑧}	Q_{gs}		-	1.4	2.1	
Gate-drain charge ^{⑦⑧}	Q_{gd}		-	1.7	2.5	

Source-Drain Diode Ratings and Characteristics

Characteristic	Symbol	Test Condition	Min	Typ	Max	Unit
Source current	I_S	Integral reverse diode in the MOSFET	-	-	-1.5	A
Source current (Pulsed) ^⑤	I_{SM}		-	-	-6.0	
Forward voltage ^⑥	V_{SD}	$V_{GS}=0V, I_S=-1.5A$	-	-	-1.2	V
Reverse recovery time	t_{rr}	$I_S=-1.5A, di_s/dt=100A/us$	-	90	-	ns
Reverse recovery charge	Q_{rr}		-	0.5	-	μC

Note ;

- ⑤ Repetitive Rating : Pulse Width Limited by Maximum Junction Temperature
- ⑥ $L=2.0mH, I_{AS}=-5.0A, V_{DD}=-15V, R_G=25\Omega$
- ⑦ Pulse Test : Pulse Width < 300us, Duty cycle \leq 2%
- ⑧ Essentially independent of operating temperature

N-CH Electrical Characteristic Curves

Fig. 1 $I_D - V_{DS}$




Fig. 2 $I_D - V_{GS}$




Fig. 3 $R_{DS(on)} - I_D$




Fig. 4 $I_S - V_{SD}$




Fig. 5 Capacitance - V_{DS}




Fig. 6 $V_{GS} - Q_G$




Fig. 7 $V_{DSS} - T_J$




Fig. 8 $R_{DS(on)} - T_J$




Fig. 9 $I_D - T_a$




Fig. 10 Safe Operating Area




Fig. 11 Gate Charge Test Circuit & Waveform




Fig. 12 Resistive Switching Test Circuit & Waveform




Fig. 13 EAS Test Circuit & Waveform





Fig. 14 Diode Reverse Recovery Time Test Circuit & Waveform



P-CH Electrical Characteristic Curves

Fig. 1 $I_D - V_{DS}$




Fig. 2 $I_D - V_{GS}$




Fig. 3 $R_{DS(on)} - I_D$




Fig. 4 $I_S - V_{SD}$




Fig. 5 Capacitance - V_{DS}




Fig. 6 $V_{GS} - Q_G$




Fig. 7 $V_{DSS} - T_J$




Fig. 8 $R_{DS(on)} - T_J$




Fig. 9 $I_D - T_a$




Fig. 10 Safe Operating Area




Fig. 11 Gate Charge Test Circuit & Waveform




Fig. 12 Resistive Switching Test Circuit & Waveform




Fig. 13 E_{AS} Test Circuit & Waveform






Fig. 14 Diode Reverse Recovery Time Test Circuit & Waveform




Package Outline Dimensions



SYMBOL	MILLIMETER(mm)			NOTE
	MINIMUM	NOMINAL	MAXIMUM	
A	1.245	—	1.445	
A1	0.125	0.175	0.275	
b	0.320	0.420	0.520	
c	0.170	0.220	0.270	
D	4.802	4.902	5.002	
E	5.870	6.020	6.170	
E1	3.761	3.861	3.961	
e	1.270 BSC			
L	0.462	0.562	0.662	
theta	0 °	—	8 °	

※ Recommended Land Pattern [unit: mm]



The AUK Corp. products are intended for the use as components in general electronic equipment (Office and communication equipment, measuring equipment, home appliance, etc.).

Please make sure that you consult with us before you use these AUK Corp. products in equipments which require high quality and / or reliability, and in equipments which could have major impact to the welfare of human life(atomic energy control, airplane, spaceship, transportation, combustion control, all types of safety device, etc.). AUK Corp. cannot accept liability to any damage which may occur in case these AUK Corp. products were used in the mentioned equipments without prior consultation with AUK Corp..

Specifications mentioned in this publication are subject to change without notice.