




Weight: 0.30 g Unit: mm



# AND205GA

## Special Shape

### 1mm x 5mm Rectangular

**Features**

- Low power requirement
- Special shape
- All plastic molded lens
- GaP – Green
- RoHS Compliant

**Optical Characteristics (T = 25°C)**

Part Number	Color		Lens Desc.	Axial Luminous Intensity (mcd)		Test Condition (I <sub>F</sub> —mA)	Viewing Angle 2θ <sub>1/2</sub> (deg)
	LED	Lens		Min.	Typ.		
AND205GA	Green	Green	Diffused	2.0	4.0	10	110

**Absolute Maximum Ratings (T<sub>A</sub> = 25°C)**

Characteristics	Symbol	Rating	Unit
Forward Current	I <sub>F</sub>	25	mA
Reverse Voltage	V <sub>R</sub>	5	V
Power Dissipation	P <sub>D</sub>	105	mW
Operating Temperature	T <sub>Opr</sub>	-40 to +85	°C
Storage Temperature Range	T <sub>Stg</sub>	-40 to +85	°C

**Electro-Optical Characteristics (T<sub>A</sub> = 25°C)**

Characteristics	Symbol	Test Condition	AND205GA		Unit
			Typ.	Max.	
Forward Voltage	V <sub>F</sub>	I <sub>F</sub> = 20mA	2.2	2.5	V
Reverse Current	I <sub>R</sub>	V <sub>R</sub> = 5 V	–	10	μA
Peak Emission Wavelength	λ <sub>p</sub>	I <sub>F</sub> = 20mA	565	–	nm
Spectral Line Half Width	λ	I <sub>F</sub> = 20mA	30	–	nm

**Precaution**

Please be careful of the following:

1. Soldering temperature: 260°C max; Soldering time: 3 sec. max; Soldering portion of lead: up to 2 mm from the body of the device.
2. The lead can be formed up to 5 mm from the body of the device without forming stress. Soldering should be performed after the lead forming.

Product specifications contained herein may be changed without prior notice.

It is therefore advisable to contact Purdy Electronics before proceeding with the design of equipment incorporating this product.

