



CATALOGUE NUMBER	LEAD FREE VERSION
7111S0625X01	7111S0625X01LF
7311S0625X01	7311S0625X01LF

LEAD FREE VERSION:

"This product meets European Union Directives and other country regulations as described in GS-22-008"

The housing will withstand exposure to 260°C peak temperature for 10seconds in a convection reflow oven.

Sn Matte plating on solder tail for Lead Free Versions

Tol.Gén: 0mm à 10mm ±0.1mm
10 à 30mm ±0.15mm
30 à 60mm ±0.2mm
60mm et plus ±0.3mm

mat'l. code				surface	tolerance	projection	product family			
-				ISO 1302	ISO 406 ISO 1101		SMARTCARD			
ltr	ecn no	dr	date	tolerances unless otherwise specified			title			
A	F20307	DLE	2002/04/30	angles	linear	mm	S06			
B	I05-0167	NT	2005/09/23				VXX27869			
C	I06-0078	DTK	2006/06/19				scale 1:1			
				dr	D LEGRAND	2002/04/30	FCI	dwg no		sheet 1 of 1
				engr	F TISSERAND	2002/04/30		VJW 53713		size
				chr	DILIPTHOMAS	2006/06/19		CUSTOMER COPY		A3
				appd	DILIPTHOMAS	2006/06/19		Drawing		
sheet index	revision	C	1							