

PNP BCY78 – BCY79

SILICON PLANAR EPITAXIAL TRANSISTORS

The BCY78 and BCY79 are PNP transistors mounted in TO-18 metal package with the collector connected to the case .

They are designed for use in audio drive and low-noise input stages.

Compliance to RoHS.

ABSOLUTE MAXIMUM RATINGS

Symbol	Ratings		Value	Unit
V_{CEO}	Collector-Emitter Voltage ($I_B = 0$)	BCY79	-45	V
		BCY78	-32	
V_{CES}	Collector-Emitter Voltage ($V_{BE} = 0$)	BCY79	-45	V
		BCY78	-32	
V_{EBO}	Emitter-Base Voltage ($I_C = 0$)	BCY79	-5	V
		BCY78	-5	
I_C	Collector Current	BCY79	-200	mA
		BCY78		
I_B	Base Current	BCY79	-20	mA
		BCY78		
P_D	Total Power Dissipation	@ $T_{amb} = 25^\circ$	390	mW
		BCY79		
P_D	Total Power Dissipation	@ $T_{case} = 45^\circ$	1	W
		BCY79		
T_J	Junction Temperature	BCY79	200	$^\circ\text{C}$
		BCY78		
T_{Stg}	Storage Temperature range	BCY79	-65 to +150	$^\circ\text{C}$
		BCY78		

THERMAL CHARACTERISTICS

Symbol	Ratings	Value	Unit
R_{thJ-a}	Thermal Resistance, Junction to mounting base	450	$^\circ\text{C}/\text{W}$
R_{thJ-c}	Thermal Resistance, Junction to ambient in free air	150	$^\circ\text{C}/\text{W}$

PNP BCY78 – BCY79

ELECTRICAL CHARACTERISTICS

T_j=25°C unless otherwise specified

Symbol	Ratings	Test Condition(s)	Min	Typ	Max	Unit				
I _{CES}	Collector Cutoff Current	V _{CB} = -35 V, V _{BE} = 0V	-	-	-20	nA				
		BCY79								
		V _{CB} = -25 V, V _B = 0V								
		BCY78								
I _{CES}	Collector Cutoff Current	V _{CB} = -35 V V _{BE} = 0V, T _j = 150°C	-	-	-10	μA				
		BCY79								
		V _{CB} = -25 V V _{BE} = 0V, T _j = 150°C								
		BCY78								
I _{EBO}	Emitter Cutoff Current	V _{BE} = -4.0 V, I _C = 0	-	-	-20	nA				
							BCY79			
V _{CEO}	Collector Emitter Breakdown Voltage	I _C = -2 mA, I _B = 0	-45	-	-	V				
							BCY79			
V _{EBO}	Emitter Base Breakdown Voltage	I _E = -1 μA, I _C = 0	-5	-	-	V				
							BCY79			
V _{CE(SAT)}	Collector-Emitter saturation Voltage	I _C = -10 mA	-	-0.12	-0.25	V				
		I _B = -0.25 mA								
		BCY79								
		BCY78								
		I _C = -100 mA	-	-0.4	-0.8	V				
		I _B = -2.5 mA								
		BCY79								
		BCY78								
V _{BE(SAT)}	Base-Emitter Saturation Voltage	I _C = -10 mA	-0.6	-0.7	-0.85	V				
		I _B = -0.25 mA								
		BCY79								
		BCY78								
		I _C = -100 mA	-0.7	-0.85	-1.2	V				
		I _B = -2.5 mA								
		BCY79								
		BCY78								
V _{BE}	Base-Emitter Voltage	I _C = -10 μA	-	-0.55	-	V				
		V _{CE} = -5 V								
		BCY79								
		BCY78								
		I _C = -2 mA					-0.6	-0.65	-0.75	V
		V _{CE} = -5 V								
		BCY79								
		BCY78								
		I _C = -10 mA	-	-0.68	-	V				
		V _{CE} = -1 V								
		BCY79								
		BCY78								
		I _C = -100 mA	-	-0.75	-	V				
		V _{CE} = -1 V								
		BCY79								
		BCY78								

Symbol	Ratings	Test Condition(s)	BCY79VII	BCY79VIII	BCY79IX	BCY79X
			BCY78VII	BCY78VIII	BCY78IX	BCY78X
h _{FE}	DC Current Gain	I _C = -10 μA, V _{CE} = -5 V	-	>30	>40	>100
			Typ.140	Typ.200	Typ.270	Typ.390
		I _C = -2 mA, V _{CE} = -5 V	>120	>180	>250	>380
			<220	<310	<460	<630
		I _C = -10 mA, V _{CE} = -1 V	>80	>120	>160	>240
	-	<400	<630	<1000		
h _{fe}	Small-Signal Current Gain	I _C = 2 mA, V _{CE} = 5 V f = 1kHz	>125	>175	>250	>350
			<250	<350	<500	<700

PNP BCY78 – BCY79

ELECTRICAL CHARACTERISTICS


T_j=25°C unless otherwise specified

Symbol	Ratings	Test Condition(s)	Min	Typ	Max	Unit		
f _T	Transition frequency	I _C = -10 mA, V _{CE} = -5 V f = 100MHz	BCY79 BCY78	-	180	-	MHz	
F	Noise figure , R _S =2kΩ	I _C = -200 μA, V _{CE} = -5 V f = 1kHz, B = 200Hz	BCY79 BCY78	-	2	6	db	
t _d	Delay time	I _{Con} = -10 mA I _{Bon} = -I _{Boff} = -1mA V _{BB} = 3.6 V R ₁ = R ₂ = 5kΩ R _L = 990 Ω	BCY79 BCY78	-	35	-	ns	
t _r	Rise time		BCY79 BCY78	-	50	-		
t _{on}	Turn on time		BCY79 BCY78	-	85	150		
t _s	Storage time		BCY79 BCY78	-	400	-		
t _f	Fall time		BCY79 BCY78	-	80	-		
t _{off}	Turn off time		BCY79 BCY78	-	480	800		
t _d	Delay time		BCY79 BCY78	-	5	-		ns
t _r	Rise time		BCY79 BCY78	-	50	-		
t _{on}	Turn on time		BCY79 BCY78	-	55	150		
t _s	Storage time		BCY79 BCY78	-	250	-		
t _f	Fall time	BCY79 BCY78	-	200	-			
t _{off}	Turn off time	BCY79 BCY78	-	450	800			
C _C	Collector capacitance	I _E = I _e = 0 , V _{CB} = -10 V f = 1MHz	BCY79 BCY78	-	-	5	pF	
C _E	Emitter capacitance	I _C = I _c = 0 , V _{EB} = -0.5 V f = 1MHz	BCY79 BCY78	-	-	15	pF	

PNP BCY78 – BCY79

ECHANICAL DATA CASE TO-18

DIMENSIONS (mm)		
	min	max
A	12.7	-
B	-	0.49
C	0.9	-
D	-	5.3
E	-	4.9
F	-	5.8
G	2.54	-
H	-	1.2
I	-	1.16
L	45°	-



Pin 1 :	emitter
Pin 2 :	base
Pin 3 :	Collector
Case :	Collector




Fig.1 Simplified outline (TO-18) and symbol.

Revised September 2012

Information furnished is believed to be accurate and reliable. However, Comset Semiconductors assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may results from its use. Data are subject to change without notice. Comset Semiconductors makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Comset Semiconductors assume any liability arising out of the application or use of any product and specifically disclaims any and all liability, including without limitation consequential or incidental damages. Comset Semiconductors' products are not authorized for use as critical components in life support devices or systems.