

Description: Tinned Copper conductor, FEP Insulation, conductors cabled, overall foil shield and FEP Jacketed Plenum Cable.


A. Construction:

- 1.0 Primaries:
 - 1.1 Conductor:
 - AWG 18 AWG
 - Stranding 19/30 Tinned Copper;
 - Nom. Dia .048"
 - 1.2 Insulation:
 - Material FEP
 - Nom. thickness .007"
 - Nom. OD .062"
 - 1.3 No. of conductors 3
 - 1.4 Color code Black, White, Red
- 2.0 Overall Cabling: 3 conductors cabled
 - 3.1 Separator: Polyester tape
 - 3.2 Shield: Aluminum/Polyester Tape; 100% coverage; (Aluminum Side out)
 - 3.3 Drain Wire: 20 AWG Stranded Tinned Copper
- 3.0 Jacket Material: FEP Nom. wall: .014" Color: Red
- 4.0 Overall Diameter of Cable Nom. .178"
- 5.0 Marking: Surface Print:
 - GENERAL CABLE (F) C8106 3C 18 AWG SHIELDED CMP (UL) C(UL) ---- ROHS
 - AAAAA*
 - * Indicates Shop Order number

B. Characteristics:

- 1.0 Conductor DC Resistance @20C Max. (Ohm): 5.5
- 2.0 Capacitance between conductors Nom. (pF/ft): 50
- 3.0 Capacitance Cond. To other Cond.& Shield Nom. (pF/ft): 95
- 4.0 Shield Resistance Nom.(Ohms/1000'): 7.5
- 5.0 Operating Voltage Nom.: 300 V
- 6.0 Continuous Operating Temp: 200C
- 7.0 Min. Bend Radius (inches): 1.6
- 8.0 Max. Pulling Tension Lbs: 70

C. Approvals: UL -CMP ; C(UL) CMP

REV	DATE	CHANGE DETAIL			
			 <p style="text-align: center;">General Cable 20 Forge Park, Franklin, Ma 02038 Phone: 508-541-7100 Fax: 508-541-8122</p>		
			Title:	C8106	
			Description:	3C 18 AWG Shielded Plenum Cable	
			Created By:		
A	06/29/09	Initial Release -VM	Final Approval:	VM 6/29/09	PAGE 1 of 1