XPEXAR

NOVEMBER 2006

XRK39653 GENERAL DESCRIPTION

The XRK39653 is a low voltage high performance PLL based zero delay buffer/clock generator designed for high speed clock distribution applications. It provides 9 low skew, low jitter outputs ideal for networking, computing and telecom applications.

The PLL based design allows the 9 outputs (8 clock outputs and 1 feedback output) to be phase aligned to the input reference clock. The outputs source LVCMOS compatible levels and can drive 50Ω transmission lines. If series termination is used, each output can drive up to 2 lines providing effectively a fanout of 1:16. The XRK39653's refer-

ence input accepts a LVPECL clock source.

For normal operation (PLL used to source the outputs), the feedback output (QFB) is connected to the feedback input (FB_IN). The VCO range of operation is 200 to 500MHz. This means that the input/output ranges are determined by the divider setting. If ÷4 is used, the input/output range is 50

to 125MHz (high range), if ÷8 is used the input/output range is 25 to 62.5MHz (low range).

For testing purposes two PLL bypass modes are provided. The first simply replaces the PLL output with the reference clock (PLL_EN=0, BYPASS=1). The dividers are still in

FIGURE 1. BLOCK DIAGRAM OF THE XRK39653

XRK39653 3.3V, 8-OUTPUT ZERO DELAY BUFFER

REV. 1.0.0

use. The second is a full bypass mode that has the PLL and divider operation removed (BYPASS=0). In this mode the reference clock directly sources the outputs drivers.

FEATURES

- 8 LVCMOS Clock Outputs
- 1 Feedback Output
- LVPECL reference clock input
- 25-125 MHz input/output frequency range
 - Input/Output range (÷4): 50-125MHz
 - Input/Output range (÷8): 25-62.5MHz
- 150ps max output to output skew
- Two bypass test mode options
- Fully Integrated PLL
- 3.3V Operation
- Pin compatible with MPC9653
- Industrial temp range: -40°C to +85°C
- 32-Lead TQFP Packaging





PRODUCT ORDERING INFORMATION

PRODUCT NUMBER	PACKAGE TYPE	OPERATING TEMPERATURE RANGE
XRK39653CQ	32-Lead TQFP	0°C to +70°C
XRK39653IQ	32-Lead TQFP	-40°C to +85°C

FIGURE 2. PIN OUT OF THE XRK39653





REV. 1.0.0

XRK39653 3.3V, 8-OUTPUT ZERO DELAY BUFFER

PIN DESCRIPTIONS

NUMBER	NAME	T	/PE	DESCRIPTION
1	AVDD	Power		Power supply for PLL
2	FB_IN	Input	pull-up	External PLL feedback clock input
3, 4, 5, 6	NC			
7	AGND	Power		PLL ground
8	PECL	Input		LVPECL - pos differential reference clock
9	PECL	Input		LVPECL - neg differential reference clock
10	OE	Input	pull-down	Output enable/disable and device reset
11,15, 19, 23, 27,	VDD	Power		Power supply
12, 14, 16, 18, 20, 22, 24, 26	Q[7:0]	Output		Clock outputs
13, 17, 21, 25, 29	GND	Power		Ground
28	QFB	Output		Feedback output for PLL
30	PLL_EN	Input	pull-up	PLL enable/disable select
31	BYPASS	Input	pull-up	PLL and output divider bypass select
32	VCO_SEL	Input	pull-up	VCO divider select

TABLE 1: CONTROL INPUT FUNCTION TABLE

Pin Name	0	1	Default
VCO_SEL	System Divide = 4 of VCO output	System Divide = 8 of VCO output	1
PLL_EN	PLL is bypassed and disabled. The PECL clock reference source drives the outputs through the divider blocks	PLL enabled. Normal operation. VCO out- put drives the outputs through the divider blocks	1
BYPASS	Complete bypass of the PLL and divider blocks. PECL reference clocks the outputs.	Normal operation. Dividers selected.	1
OE	Outputs enabled	Outputs tri-stated and device reset. VCO running at minimum frequency	0



SYMBOL	CHARACTERISTICS	MIN	Түр	Мах	Unit	CONDITION
V _{CMR} ^a	PECL Clock inputs common mode range	1.0		V _{DD} -0.6	V	LVPECL
V _{PP}	PECL Clock peak-to-peak input voltage	300		1000	mV	LVPECL
V _{IH}	Input voltage high	2.0		V _{DD} +0.3	V	LVCMOS
V _{IL}	Input voltage low			0.8	V	LVCMOS
V _{OH}	Output High Voltage ^a	2.4			V	I _{OH} =-24mA
V _{OL}	Output Low Voltage ^a			0.55	V	I _{OL} =24mA
				0.30	V	I _{OL} =12mA
Z _{OUT}	Output Impedance	Γ	14-17		Ω	
I _{IN}	Input leakage current			<u>+</u> 200	μA	$V_{IN} = V_{DD}$ or $V_{IN} = GND$
I _{CC_PLL}	Maximum PLL supply current		5.0	10.0	mA	AV _{DD} pin
I _{CCQ}	Maximum Quiescent supply current			10.0	mA	All V _{DD} pins, $\overline{OE}=1$
V _{TT}	Output Termination Voltage		V _{CC} ÷2		V	

DC CHARACTERISTICS (V_{CC}= $3.3 \pm 5\%$, T_A= -40°C to +85°C)

a. VCMR is the cross point of the differential input signal.

AC CHARACTERISTICS (V_{CC}= 3.3 \pm 5%, T_A= -40°C to +85°C) ^a

SYMBOL	PARAMETER		MIN	Түр	ΜΑΧ	Unit	CONDITION
f _{VCO}	VCO Frequency		200		500	MHz	
f _{ref}	Input Reference Frequency	÷4 feedback	50		125	MHz	PLL locked
		÷8 feedback	25		62.5		PLL locked
		PLL Bypass	0		200		bypass mode
f _{MAX}	Max Output Frequency	÷4 feedback	50		125	MHz	PLL locked
		÷8 feedback	25		62.5		PLL locked
V _{PP}	PECL Clock peak-to-peak input voltage		450		1000	mV	LVPECL
V _{CMR}	PECL input Common Mode range		1.2		V _{DD} -0.75	V	LVPECL
t _{PW Min}	Input Reference Clock Minimum Pulse Width		2			ns	
t _{SPO}	Propagation Delay - Static Phase Offset (PECL to FB_IN)		-75		125	ps	PLL locked
t _{PD}	Propagation Delay - PLL Bypassed						
	Bypass mode 1 ($\overline{BYPASS} = 0$)		1.2		3.3	ns	
	Bypass mode 2, (BYPASS = 1, PLL_EN = 0)		3.0		7.0	ns	
t _{skew(O)}	Output-to-Output Skew				150	ps	
t _{skew(PP)}	Part to Part Skew (bypass PLL & divider)				1.5	ns	BYPASS=0
t _{JIT(CC)}	Cycle-to-Cycle Jitter				100	ps	



REV. 1.0.0

XRK39653 3.3V, 8-OUTPUT ZERO DELAY BUFFER

AC CHARACTERISTICS (V_{CC}= 3.3 \pm 5%, T_A= -40°C to +85°C) ^a

SYMBOL	PARAMETER		ΜιΝ	Түр	ΜΑΧ	Unit	CONDITION
t _{JIT(PER)}	Period Jitter				100	ps	
t _{JIT(I/O)}	I/O Phase Jitter (RMS)				25	ps	
BW	PLL bandwidth	÷4 feedback ÷8 feedback			0.8 - 4 0.5 - 1.3	MHz MHz	
DC	Output duty cycle		45	50	55	%	PLL locked
t _{LOCK}	Maximum PLL Lock Time				10.0	ms	
t _{or} /t _{of}	Output Rise/Fall time		100		1000	ps	0.55 to 2.4V
t _{PLZ,HZ}	Output Disable Time				7	ns	
t _{PHZ,LZ}	Output Enable Time				6	ns	

a. AC characteristics apply for parallel output termination of 50Ω to V_{TT}

MAXIMUM RATINGS^a

SYMBOL	CHARACTERISTICS	Min	Мах	Unit	CONDITION
V _{DD}	Supply Voltage	-0.3	3.9	V	
V _{IN}	DC Input Voltage	-0.3	V _{DD} +0.3	V	
V _{OUT}	DC Output Voltage	-0.3	V _{DD} +0.3	V	
I _{IN}	DC Input Current		<u>+</u> 20	mA	
I _{OUT}	DC Output Current		<u>+</u> 50	mA	
Τ _S	Storage Temperature	-65	125	°C	

a. Absolute maximum continuous ratings are those maximum values beyond which damage to the device may occur. Exposure to these conditions or conditions beyond those indicated may adversely affect device reliability.

GENERAL SPECIFICATIONS

SYMBOL	CHARACTERISTICS	Min	Түр	Мах	Unit	CONDITION
V _{TT}	Output termination voltage		V _{CC} ÷2		V	
MM	ESD Protection (Machine model)	200			V	
HBM	ESD Protection (Human body model)	2000			V	
LU	Latch-up immunity				mA	
C _{IN}	Input Capacitance		4.0		pF	Inputs



FIGURE 3. OUTPUT-TO-OUTPUT SKEW t_{SK(O)}



FIGURE 4. PROPOGATION DELAY $(t_{(\emptyset)})$, STATIC PHASE OFFSET) TEST REFERENCE



FIGURE 5. OUTPUT DUTY CYCLE (DC)



FIGURE 6. I/O JITTER





FIGURE 7. CYCLE-TO-CYCLE JITTER



FIGURE 8. PERIOD JITTER



FIGURE 9. OUTPUT TRANSITION TIME TEST REFERENCE





PACKAGE DIMENSIONS



	INC	HES	MILLIN	IETERS
SYMBOL	MIN	МАХ	MIN	MAX
А	0.055	0.063	1.40	1.60
A ₁	0.002	0.006	0.05	0.15
A ₂	0.053	0.057	1.35	1.45
В	0.012	0.018	0.30	0.45
С	0.004	0.008	0.09	0.20
D	0.346	0.362	8.80	9.20
D ₁	0.272	0.280	6.90	7.10
е	0.0315 BSC		0.80	BSC
L	0.018	0.030	0.45	0.75
α	0°	7 °	0°	7 °

Note: The control dimension is the millimeter column



REV. 1.0.0

REVISION HISTORY

REVISION #	DATE	DESCRIPTION
1.0.0	November 2006	Initial FINAL release.

NOTICE

EXAR Corporation reserves the right to make changes to the products contained in this publication in order to improve design, performance or reliability. EXAR Corporation assumes no responsibility for the use of any circuits described herein, conveys no license under any patent or other right, and makes no representation that the circuits are free of patent infringement. Charts and schedules contained here in are only for illustration purposes and may vary depending upon a user's specific application. While the information in this publication has been carefully checked; no responsibility, however, is assumed for inaccuracies.

EXAR Corporation does not recommend the use of any of its products in life support applications where the failure or malfunction of the product can reasonably be expected to cause failure of the life support system or to significantly affect its safety or effectiveness. Products are not authorized for use in such applications unless EXAR Corporation receives, in writing, assurances to its satisfaction that: (a) the risk of injury or damage has been minimized; (b) the user assumes all such risks; (c) potential liability of EXAR Corporation is adequately protected under the circumstances.

Copyright 2006 EXAR Corporation

Datasheet November 2006.

Reproduction, in part or whole, without the prior written consent of EXAR Corporation is prohibited.