



### Silicon Standard Recovery Diode

$V_{RRM} = 50\text{ V} - 600\text{ V}$   
 $I_F = 60\text{ A}$

#### Features

- High Surge Capability
- Types up to 600 V  $V_{RRM}$

DO-5 Package

#### Note:

1. Standard polarity: Stud is cathode.
2. Reverse polarity (R): Stud is anode.
3. Stud is base.



#### Maximum ratings, at $T_J = 25\text{ }^\circ\text{C}$ , unless otherwise specified

Parameter	Symbol	Conditions	1N2128A(R)	1N2129A(R)	1N2130A(R)	1N2131A(R)	Unit
Repetitive peak reverse voltage	$V_{RRM}$		50	100	150	200	V
RMS reverse voltage	$V_{RRMS}$		35	70	106	140	V
DC blocking voltage	$V_{DC}$		50	100	150	200	V
Continuous forward current	$I_F$	$T_C \leq 150\text{ }^\circ\text{C}$	60	60	60	60	A
Surge non-repetitive forward current, Half Sine Wave	$I_{F,SM}$	$T_C = 25\text{ }^\circ\text{C}$ , $t_p = 8.3\text{ ms}$	1050	1050	1050	1050	A
Operating temperature	$T_J$		-65 to 200	-65 to 200	-65 to 200	-65 to 200	$^\circ\text{C}$
Storage temperature	$T_{stg}$		-65 to 200	-65 to 200	-65 to 200	-65 to 200	$^\circ\text{C}$

#### Electrical characteristics, at $T_J = 25\text{ }^\circ\text{C}$ , unless otherwise specified

Parameter	Symbol	Conditions	1N2128A(R)	1N2129A(R)	1N2130A(R)	1N2131A(R)	Unit
Diode forward voltage	$V_F$	$I_F = 60\text{ A}$ , $T_J = 25\text{ }^\circ\text{C}$	1.1	1.1	1.1	1.1	V
Reverse current	$I_R$	$V_R = 50\text{ V}$ , $T_J = 25\text{ }^\circ\text{C}$	10	10	10	10	$\mu\text{A}$
		$V_R = 50\text{ V}$ , $T_J = 150\text{ }^\circ\text{C}$	15	15	15	15	mA

#### Thermal characteristics

Thermal resistance, junction - case	$R_{\theta JC}$		0.85	0.85	0.85	0.85	$^\circ\text{C/W}$
-------------------------------------	-----------------	--	------	------	------	------	--------------------



Figure 1-Typical Forward Characteristics




Figure 2-Forward Derating Curve




Figure 3-Peak Forward Surge Current




Figure 4-Typical Reverse Characteristics

