

Customer Information Sheet

DRAWING No.: D01-950XX01

SHEET 2 OF 2


IF IN DOUBT - ASK

©

NOT TO SCALE

THIRD ANGLE PROJECTION

ALL DIMENSIONS IN mm



SPECIFICATIONS:

MATERIAL:
 MOULDING = GLASS-FILLED POLYESTER
 UL94V-0, BLACK

SHELL = BRASS
 CLIP = BERYLLIUM COPPER

FINISH:
 SHELL = 5µ 90/10 TIN/LEAD
 CLIP = 0.75µ GOLD

ELECTRICAL:
 CURRENT RATING = 1A
 VOLTAGE RATING = 100V AC, 150V DC
 CONTACT RESISTANCE = 10 MILLIOHMS MAX.
 INSULATION RESISTANCE = 10,000 MEGOHMS MIN.
 DIELECTRIC WITHSTANDING = 1,000V AC MIN.

MECHANICAL:
 INSERTION FORCE (Ø0.43mm GAUGE) = 3.0N MAX
 WITHDRAWAL FORCE (Ø0.43mm GAUGE) = 0.5N MIN
 DURABILITY = 100 CYCLES MIN

ENVIRONMENTAL:
 TEMPERATURE RANGE = -55 TO +125°C

NOTES:

1. RECOMMENDED HOLE SIZE = Ø0.80mm.
2. RECOMMENDED PC BOARD THICKNESS = 1.4 TO 2.0mm.
3. RECOMMENDED MATING PIN DIAMETER = Ø0.56-Ø0.40mm.
4. MAXIMUM CONTACT DEPTH = 2.40mm,
 MAXIMUM MATING PIN LENGTH = 3.65mm.
5. FOR COMPLETE SPECIFICATION, SEE COMPONENT SPECIFICATION C004XX (LATEST ISSUE).

ORDER CODE:
 D01-950XX01

No. OF WAYS _____
 04-10, 12, 14, 16, 18, 20, 32

FINISH _____
 01 - TIN/LEAD SHELL, GOLD CLIP

1	07.09.00	----
ISS.	DATE	C/NOTE
APPROVED:		
CHECKED:		
DRAWN: W. J. BOURNE		
CUSTOMER REF.:		
ASSEMBLY DRG:		



HARWIN INC
 U.S.A.
 TEL: (812) 285 0055
 FAX: (812) 285 0056

HARWIN PLC
 U.K.
 TEL: 023 9237 0451
 FAX: 023 9231 4590

HARWIN PTE
 SINGAPORE
 TEL: 65 7794909
 FAX: 65 7793868

THIS DRAWING AND ANY INFORMATION OR DESCRIPTIVE MATTER SET OUT HEREON ARE CONFIDENTIAL AND COPYRIGHT PROPERTY OF THE HARWIN GROUP AND MUST NOT BE DISCLOSED, LOANED, COPIED OR USED FOR MANUFACTURING, TENDERING OR FOR ANY OTHER PURPOSE WITHOUT THEIR WRITTEN PERMISSION.

TOLERANCES
 X. = ±1mm
 X.X = ±0.25mm
 X.XX = ±0.10mm
 X.XXX = ±0.01mm
 ANGLES = ±1°
 UNLESS STATED

MATERIAL:
 SEE ABOVE

FINISH: SEE ABOVE

S/AREA: mm²

TITLE: 2.54mm PITCH SIL
 EXTENDED VERTICAL PC TAIL
 SOCKET ASSEMBLY

DRAWING NUMBER:
 D01-950XX01

SHT
 2
 OF
 2