



Part No.	Material	λ D (nm)	Lens Type	Iv (mcd) @70mA *50mA		Viewing Angle 2θ1/2	Dimension
				Min.	Typ.		

L-7677C2SEC-H	InGaAlP	630	water clear	10000	20000	30°	7.62mm x 7.62mm
L-7677C2SYC-H	InGaAlP	589	water clear	1500	5000	30°	
L-7677C2SURC-G	InGaAlP	630	water clear	4700	8000	30°	
L-7677C2PBC-Z-DTS	InGaN	465	water clear	*5700	*9500	15°	
L-7677C2VGC-Z	InGaN	535	water clear	*10000	*25000	30°	

L-7678C2SEC-H	InGaAlP	630	water clear	7500	18000	40°	7.62mm x 7.62mm
L-7678C2SYC-H	InGaAlP	589	water clear	1200	4500	40°	
L-7678C2SURC-G	InGaAlP	630	water clear	2500	4500	40°	
L-7678C2PBC-Z-DTS	InGaN	465	water clear	*3300	*7000	30°	
L-7678C2VGC-Z	InGaN	535	water clear	*10000	*23000	40°	

L-7679C1SEC-H	InGaAlP	630	water clear	6500	8000	70°	7.62mm x 7.62mm
L-7679C1SYC-H	InGaAlP	589	water clear	1200	4000	70°	
L-7679C1SURC-G	InGaAlP	630	water clear	1800	3000	70°	
L-7679C1PBC-Z-DTS	InGaN	465	water clear	*900	*2500	50°	
L-7679C1VGC-Z	InGaN	535	water clear	*5700	*10000	70°	

NOTES:

1. All dimensions are in millimeters(inches).
2. Tolerance is ±0.25mm(0.01") unless otherwise noted.