



ICH SERIES

TYPE CARRIER

ICH
= Hi-Temp Polyester

ROW SPACE

-2 thru -19

= Row Spacing

Row Spacing EXAMPLE:
-3 = .300 centers

NO. OF PINS

02 thru 40

= Total Number of Pins

LEAD STYLE

-S or -A

= Printed Circuit

For LIF Specify -ZS or -ZA

LEAD STYLE	Y TAIL	Z
-S or -ZS	(3.18) 125	(7.62) 300
-A or -ZA	(4.57) 180	(8.89) 350

Locking lead (-L) available. See OPTION.

-B

= Body Only

For LIF Specify -ZB

-P or -T

= Short Tail

For LIF Specify -ZP or -ZT

N/A Single Row

LEAD STYLE	Z
-P or -ZP	(5.20) 205
-T or -ZT	(4.24) 167

Locking lead (-L) available. See OPTION.

PLATING OPTION

GG

= 30μ" Gold Contact
10μ" Gold Shell

GT

= 30μ" Gold Contact
200μ" Tin Shell

TT

= 200μ" Tin Contact and Shell
(Styles -S, -ZS, -C, -A, -L, -M, -N only)

ST

= 10μ" Gold Contact
200μ" Tin Shell
(Styles -S & -ZS only)

OPTION

(Leave Blank for Standard Version)

-L

= Locking Socket

Requires Style -S, -ZS, -P or -ZT and .035"±.003" board hole.

Low Insertion Force (LIF) Contacts Available.

SAMTEC USA • Tel: 1-800-SAMTEC-9 or 812-944-6733 • Fax: 812-948-5047 **SAMTEC UK** • Tel: 01236 739292 • Fax: 01236 727113 **SAMTEC ASIA PACIFIC** • Tel: 65-745-5955 • Fax: 65-841-1502
SAMTEC GERMANY • Tel: +49 (0) 89 / 89460-0 • Fax: +49 (0) 89 / 89460-299 **SAMTEC FRANCE** • Tel: 01 60 95 06 60 • Fax: 01 60 95 06 61 **SAMTEC ITALY** • Tel: 39 039 6890337 • Fax: 39 039 6890315
SAMTEC JAPAN • Tel: 81-424-42-8318 • Fax: 81-424-42-8319 **SAMTEC CHINA** • Tel: 86-21-5385-4089 • Fax: 86-21-5385-4047 **SAMTEC TAIWAN** • Tel: (02) 2395-1677 • Fax: (02) 2395-1689

Due to technical progress, all designs, specifications and components are subject to change without notice.