



HONEYWELL
PART NUMBER
11SM4601-H4
PRODUCT CODE
TWZ2610

REV	DOCUMENT	CHANGED BY	CHECK
6	0038224	KVS 22APR08	ASD



NOTE -

- ^Δ - MOUNTING HOLES WILL ACCEPT PINS OR SCREWS OF .087 MAX DIA ON .375 ± .002 CENTERS
- 2 - TERMINALS ARE PLATED FOR SOLDERING
- 3 - DEAD BREAK CONDITIONS:
 - A - MAX AMOUNT PERMISSIBLE ----- .0002 IN
 - B - LOAD ----- 10 VAC
.035 AMPS
 - C - PLUNGER TRAVEL RATE ----- .015 IN. PER MINUTE

RELEASE NO. PR - 6102

REPLACES

CHARACTERISTICS	
OPERATING FORCE	--- 3 1/2 OZ MAX
RELEASE FORCE	--- 1 OZ MIN
DIFFERENTIAL TRAVEL	--- .001 MAX
OVERTRAVEL	--- .005 MIN

ELECTRICAL DATA		
CONTACT ARRANGEMENT SPDT		
30 VOLTS DC RATING		
	SEA LEVEL	50,000 FT
INDUCTIVE	3 AMP	2.5 AMP
RESISTIVE	5 AMP	5 AMP
MAXIMUM INRUSH 24 AMP		
APPROVALS	KEMA, CE	5A, 250V ~ T85 1E4
	UL, CSA	5A, 250 VAC

DESIGN UNITS: INCH
TOLERANCES UNLESS NOTED:
NO PLACE X ±
ONE PLACE .X ±
TWO PLACE .XX ±
THREE PLACE .XXX ±
FOUR PLACE .XXXX ±
ANGLES ±
THIRD ANGLE PROJECTION

DRAWN	VK	27 NOV 07
CHECK	RJ	27 NOV 07
THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE PERMISSION OF HONEYWELL.		
INTERPRET PER ANSI Y14.5M-1982 OTHER HONEYWELL ENGINEERING STANDARDS MAY APPLY		
RASTER		

Honeywell			
TITLE SWITCH - BASIC			
SIZE	TYPE	DRAWING NAME	REV
B	I	11SM4601-H4	6
SCALE	-	WEIGHT .006 LB MAX	SHEET 1 OF 1