



Transient Voltage Suppressors

3.0SMC Series

Transient Voltage Suppressors - 3.0SMC Series

Features

1. Halogen-free
2. Rohs compliant
3. Typical maximum temperature coefficient
4. $\Delta V_{BR} = 0.1\% \times V_{BR@25^{\circ}C} \times \Delta T$
5. Glass passivated Chip junction in DO-214AB package
6. 3000W peak pulse capability at 10x1000μs waveform, repetition rate (duty cycles):0.01%
7. Fast response time:typically less than 1.0ps from 0 Volts to BV min
8. Excellent clamping capability
9. Low incremental surge resistance
10. Typical IR less than 5μA above 12V
11. High temperature soldering guaranteed:260°C/40seconds/0.375", (9.5 mm) lead length, 5lbs., (2.3kg) tension
12. Plastic package has underwriters laboratory flammability classification 94v-0



Applications

TVS devices are ideal for the protection of I/O interfaces,VCC bus and other vulnerable circuits used in telecom, computer, industrial and consumer electronic applications.

Mechanical Characteristics

Rating	Symbol	Value	Units
Peak Pulse Power Dissipation by 10x1000μs test waveform (Fig.1)(Note 1)	P_{PPM}	3000	Watts
Steady State Power Dissipation on infinite heat sink at TL=75°C (Fig. 5)	P_D	6.5	Watts
Peak Forward Surge Current, 8.3ms Single Half Sine Wave Unidirectional only (Note 2)	I_{FSM}	300	Amps
Maximum Instantaneous Forward Voltage at 25A for Unidirectional only (Note 3)	V_F	3.5	V
Operating junction and Storage Temperature Range.	T_J, T_{STG}	-55°C to 175°C	°C
Typical Thermal Resistance Junction to Lead	$R_{\theta JL}$	15	°C/W
Typical Thermal Resistance Junction to Ambient	$R_{\theta JA}$	75	°C/W

Notes:

1. Non-repetitive current pulse , per Fig. 3 and derated above TA = 25°C per Fig. 2.
2. Mounted on copper pad area of 0.31x0.31" (8.0 x 8.0mm) to each terminal.
3. Measured on 8.3ms single half sine wave or equivalent square wave for unidirectional device only, duty cycle=4 per minute maximum.

Transient Voltage Suppressors - 3.0SMC Series

Electrical Characteristics

Type Number		Reverse Stand-Off Voltage	Breakdown Voltage@I _T		Test Current	Maximum Clamping Voltage@I _{PP}	Peak Pulse Current	Reverse Leakage @V _{RWM}
(UNI)	(BI)		V _{RWM} (V)	V _{BR MIN.} (V)				
3.0SMC6.8A	3.0SMC6.8CA	5.80	6.40	7.25	10	9.2	326.1	800
3.0SMC7.5A	3.0SMC7.5CA	6.40	7.22	8.30	10	11.2	267.3	800
3.0SMC8.2A	3.0SMC8.2CA	7.02	7.78	8.95	10	12.0	250.0	200
3.0SMC9.1A	3.0SMC9.1CA	7.78	8.33	9.58	1	12.9	232.6	100
3.0SMC10A	3.0SMC10CA	8.55	9.44	10.82	1	13.6	220.6	50
3.0SMC11A	3.0SMC11CA	9.40	10.00	11.50	1	18.2	164.8	5
3.0SMC12A	3.0SMC12CA	10.20	11.10	12.80	1	19.9	150.8	5
3.0SMC13A	3.0SMC13CA	11.10	12.20	14.00	1	21.5	139.5	5
3.0SMC15A	3.0SMC15CA	12.80	14.40	16.50	1	24.4	123.0	5
3.0SMC16A	3.0SMC16CA	13.60	15.60	17.90	1	26.0	115.4	5
3.0SMC18A	3.0SMC18CA	15.30	16.70	19.20	1	29.2	102.7	5
3.0SMC20A	3.0SMC20CA	17.10	18.90	21.70	1	32.4	92.6	5
3.0SMC22A	3.0SMC22CA	18.80	20.00	23.30	1	35.5	84.5	5
3.0SMC24A	3.0SMC24CA	20.50	22.20	25.50	1	38.9	77.1	5
3.0SMC27A	3.0SMC27CA	23.10	24.40	28.00	1	42.1	71.3	5
3.0SMC30A	3.0SMC30CA	25.60	28.90	33.20	1	48.4	62.0	5
3.0SMC33A	3.0SMC33CA	28.20	31.10	35.80	1	53.3	56.3	5
3.0SMC36A	3.0SMC36CA	20.80	33.30	38.30	1	58.1	51.6	5
3.0SMC39A	3.0SMC39CA	33.30	36.70	42.20	1	64.5	46.5	5
3.0SMC43A	3.0SMC43CA	36.80	40.00	46.00	1	69.4	43.2	5
3.0SMC47A	3.0SMC47CA	40.20	44.40	51.10	1	72.7	41.3	5
3.0SMC51A	3.0SMC51CA	43.60	47.80	54.90	1	82.4	36.4	5
3.0SMC56A	3.0SMC56CA	47.80	50.00	57.50	1	87.1	34.4	5
3.0SMC62A	3.0SMC62CA	53.00	56.70	65.20	1	96.8	31.0	5
3.0SMC68A	3.0SMC68CA	58.10	64.40	74.10	1	103.0	29.1	5
3.0SMC75A	3.0SMC75CA	64.10	71.10	81.80	1	121.0	24.8	5
3.0SMC82A	3.0SMC82CA	70.10	77.80	89.50	1	137.0	20.8	5
3.0SMC91A	3.0SMC91CA	77.80	86.70	99.70	1	146.0	20.6	5
3.0SMC100A	3.0SMC100CA	85.50	94.40	108.20	1	162.0	18.6	5
3.0SMC110A	3.0SMC110CA	94.00	100.00	115.50	1	177.0	16.8	5
3.0SMC120A	3.0SMC120CA	102.00	111.00	128.00	1	193.0	15.6	5
3.0SMC130A	3.0SMC130CA	111.00	122.00	140.50	1	209.0	14.4	5
3.0SMC150A	3.0SMC150CA	128.00	144.00	165.50	1	243.0	12.4	5
3.0SMC180A	3.0SMC180CA	154.00	167.00	192.60	1	292.0	10.3	5
3.0SMC200A	3.0SMC200CA	171.00	189.00	217.50	1	324.0	9.3	5
3.0SMC220A	3.0SMC220CA	185.00	209.00	243.20	1	356.0	8.4	5

Transient Voltage Suppressors - 3.0SMC Series

Ratings and Characteristic Curves

Figure 1 - Peak Pulse Power Rating Curve




Figure 2 - Pulse Derating Curve




Figure 3 - Pulse Waveform




Figure 4 - Typical Junction Capacitance




Figure 5 - Steady State Power Derating Curve






Figure 6 - Maximum Non-Repetitive Peak Forward Surge Current Uni-Directional Only



Transient Voltage Suppressors - 3.0SMC Series

Soldering Parameters

	Reflow Condition	Lead-free assembly
Pre Heat	- Temperature Min ($T_{s(min)}$)	150°C
	- Temperature Max ($T_{s(max)}$)	200°C
	- Time (min to max) (t_s)	60-180 secs
Average ramp up rate (Liquidus Temp (T_L) to peak)		3°C/second max
$T_{s(max)}$ to T_L - Ramp-up Rate		3°C/second max
Reflow	- Temperature (T_L) (Liquidus)	217°C
	- Time (min to max) (t_s)	60-150 seconds
Peak Temperature (T_p)		260 ^{+0/-5} °C
Time within 5°C of actual peak Temperature (t_p)		20-40 seconds
Ramp-down Rate		6°C/second max
Time 25°C to peak Temperature (T_p)		8 minutes Max.
Do not exceed		280°C



Physical Specifications


Weight	0.007 ounce, 0.21 grams
Case	JEDEC DO214AB. Molded plastic body over glass passivated junction
Polarity	Color band denotes cathode except Bidirectional.
Termination	Matte Tin-plated leads, Solderable per JESD22-B102D

Environmental Specifications

Temperature Cycle	JESD22-A104
Pressure Cooker	JESD 22-A102
High Temp. Storage	JESD22-A103
HTRB	JESD22-A108
Thermal Shock	JESD22-A106

Transient Voltage Suppressors - 3.0SMC Series

Dimensions



Unit:mm

DIM	Inches		Millimeters	
	Min	Max	Min	Max
A	0.114	0.126	2.900	3.200
B	0.260	0.280	6.600	7.110
C	0.220	0.245	5.590	6.220
D	0.079	0.103	2.060	2.620
E	0.030	0.060	0.760	1.520
F	-	0.008	-	0.203
G	0.305	0.320	7.750	8.130
H	0.006	0.012	0.152	0.305
I	0.129	-	3.300	-
J	0.094	-	2.400	-
K	-	0.165	-	4.200
L	0.094	-	2.400	-

Warehouse Storage Conditions of Products

- Storage Conditions:
 1. Storage Temperature: -10°C~+40°C
 2. Relative Humidity:≤75%RH
 3. Keep away from corrosive atmosphere and sunlight.
- Period of Storage: 1 year

RuiLongYuan Electronics Co., Ltd.

- Reproducing and modifying information of the document is prohibited without permission from Ruilongyuan International Inc.
- Ruilongyuan International Inc. reserves the rights to make changes of the content herein the document anytime without notification. Please refer to our website for the latest document.
- Ruilongyuan International Inc. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Ruilongyuan International Inc. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Ruilongyuan International Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Ruilongyuan International Inc. for any damages resulting from such improper use or sale.

Tel: +86-755-8290 8296

Fax: +86-755-8290 8002

E-mail: jack@ruilon.com